



Oregon Department of Transportation
 3930 Fairview Industrial Dr SE
 Salem OR 97302-1166

Pilot Vehicle and TCP Requirements

**US20 Central Oregon Highway
 HWY 007 (MP 0.51 – MP 131.50)
 Bend to Burns**

Width:	Requirements:
UP TO 16'	ONE FRONT AND ONE REAR PILOT CARS MINIMUM
16'1" – 17'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM
17'1" – 18'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 48.37 – MP 62.07 MP 68.97 – MP 90.90 MP 101.83 – MP 127.70 FULL CLOSURE
18'1" – 19'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 25.65 – MP 29.04 MP 48.37 – MP 127.70 FULL CLOSURE
19'1" – 20'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 25.65 – MP 29.04 MP 48.37 – MP 127.70 FULL CLOSURE
20'1" – 21'	THREE FRONT AND ONE REAR PILOT CARS MINIMUM EXCEPT: MP 2.87 – MP 4.30 MP 27.18 – MP 127.70 FULL CLOSURE
21'1" and OVER	CASE BY CASE AT DISTRICT DISCRETION (THREE FRONT AND ONE REAR MINIMUM)

Additional Limitations & Exceptions:

Over-Dimension Permit analysts allowed to permit travel on US20 from MP 0.51 to MP 131.50, up to 17' wide without calling the District; provided the axle width does not exceed 12' wide and the overall length does not exceed 150'.

Loads exceeding the above dimensions will be individually evaluated by District personnel based on specific characteristics of load and hauling equipment.