

Oregon Department of Transportation - Approved Product List

Updated September 22, 2026

These Chargers and Networks meet the program requirements established by Oregon Department of Transportation for Round 5 of the Community Charging Rebate (CCR) program.

All equipment must:

- Be new and installed for the first time. Previously installed or rebuilt equipment is ineligible. Replacement of broken equipment is eligible, but projects must still follow the minimum port requirements.
- Be purchased and not leased.
- **Have a minimum two-year warranty**, either from the manufacturer, a third party, or the contractor. ODOT strongly encourages extended warranties.

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
Autel	AC W12-L-4G	AC Elite	AC	12	✓	⚠	Single Port ; OCPP Full Certificate with software version V1.13.97
Autel	Maxi UW19#002	MaxiCharger AC Pro 80A	AC	19.2	✓	✗	Single port. Where '#' can be substituted for the following characters: - 'C': 19ft cable, J1772 - 'L': 25ft cable, J1772 - 'M': 25ft cable, NACS
Autel	Maxi UW19CJ02	MaxiCharger AC 80A	AC	19.2	✓	✗	Single port.
Autel	Maxi UW19LJ02	MaxiCharger AC 80A	AC	19.2	✓	✗	Single port.
Autel	UF####101	AC Ultra	AC	19.2	✓	⚠	Single Port or Dual Port
Blink	780	Series 7 ISO Single	AC	19.2	✓	✓	Single port.
Blink	ZM10048	Blink Shasta 48	AC	11.52	✓	✓	Level 2 EVSE; configurable up to 48A; J1772 or NACS connector; OCPP 1.6 / 2.0.1; ISO 15118 hardware ready; Ethernet, Wi-Fi, and 4G LTE connectivity; RFID authentication; 7" touchscreen; UL 2594 certified; NIST HB 44 compliant; Energy Star and NTEP pending
Blink	ZM10080	Blink Shasta 80	AC	19.2	✓	✓	connector; OCPP 1.6 / 2.0.1; ISO 15118 hardware ready; Ethernet, Wi-Fi, and 4G LTE connectivity; RFID authentication; 7" touchscreen; UL 2594 certified; NIST
Blink	IQW2-80U-M1-R2-N-25 (Advanced-LTE) Part Number 01-0207-LTE (IQ 200 Advanced)	IQ 200 Advanced	AC	19.2	✓	⚠	Single Port
Blink	780 (40A)	Series 7 ISO (Enhanced)	AC	9.6	✓	⚠	Dual Port, Standalone network capability
Blink	780 (48A)	Series 7 ISO (Enhanced)	AC	11.52	✓	⚠	Dual Port, Standalone network capability
Blink	780 Series	Series 7 ISO Plus	AC	19.2	✓	⚠	Dual Port, Standalone network capability
Blink	880 (40A)	Series 8 ISO (Enhanced)	AC	9.6	✓	⚠	Single or dual Port, Standalone network capability

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
Blink	880 (48A)	Series 8 ISO (Enhanced)	AC	11.52	✓	⚠	Dual Port, Standalone network capability
Blink	880 (80A)	Series 8 ISO Plus	AC	19.2	✓	⚠	Dual Port, Standalone network capability
ChargePoint	CP6####-50A-L##	6000 Series	AC	12	✓	⚠	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CP6####-80A-L##	6000 Series	AC	19.2	✓	⚠	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
ChargePoint	CPF50- L##-*****	CPF50	AC	12	✓	⚠	CPF50 family, Single or Dual Port, Pedestal or Wall Mount, 50A, Type 1, Cable 18' or 23', Single Phase Charger, Cable Management Kit optional
ChargeSmart EV	CSEV-ACPro	CSEV-ACPro	AC	19.2	✓	✗	Single port.
ChargeSmart EV	CSEV-ACPro	CSEV-ACPro	AC	19.2	✓	✗	Single port.
CyberSwitching	CSE4-4G-BL	CSE4	AC	19.2	✓	✓	Single Port
CyberSwitching	CSE1-4G-BL	CSE1	AC	11.5	✓	✓	Single Port
CyberSwitching	CSE1-WIFI-BL	CSE1	AC	11.5	✓	✓	Single Port
Eaton	CP6####-50A-L##-ETN	6000 Series	AC	12	✓	⚠	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
Eaton	CP6####-80A-L##-ETN	6000 Series	AC	19.2	✓	⚠	CP6000 family, NA, AC Station, 1 or 2 x Type 1 Cable, 50A or 80A, 1-Phase, 18' or 23' Cable, 6' or 8' Cable Management Kit, Pedestal or Wall Mount, 8" Touch Display, Contactless Credit Card and RFID Reader, Cellular/Wi-Fi, UL, Power Share Jumper, 1YR Parts Warranty, Optional credit card reader
Eaton	CPF50- L##-*****-ETN	CPF50	AC	12	✓	⚠	CPF50 family, Single or Dual Port, Pedestal or Wall Mount, 50A, Type 1, Cable 18' or 23', Single Phase Charger, Cable Management Kit optional
Eaton	GMEV40CIE1 B-WC/ GMEV40CIC1 B-WC	Green Motion EV Charger	AC	9.6	✓	⚠	
Eaton	GMEV40CME1 B-WC/ GMEV40CMC1 B-WC/ GMEV40CMX1 B-WC	Green Motion EV Charger	AC	9.6	✓	⚠	

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
Eaton	GMEV80CIE1 B-WC/ GMEV80CIC1 B-WC	Green Motion EV Charger	AC	19.2	✓	⚠	
Eaton	GMEV80CMC 1B-AA	Green Motion EV Charger	AC	19.2	✓	⚠	AB Phasing/Cellular
Eaton	GMEV80CMC 1B-AB	Green Motion EV Charger	AC	19.2	✓	⚠	BC Phasing/Cellular
Eaton	GMEV80CMC 1B-AC	Green Motion EV Charger	AC	19.2	✓	⚠	CA Phasing/Cellular
Eaton	GMEV80CME 1B-AA	Green Motion EV Charger	AC	19.2	✓	⚠	AB Phasing/Wi-Fi
Eaton	GMEV80CME 1B-AB	Green Motion EV Charger	AC	19.2	✓	⚠	BC Phasing/Wi-Fi
Eaton	GMEV80CME 1B-AC	Green Motion EV Charger	AC	19.2	✓	⚠	CA Phasing/Wi-Fi
Eaton	GMEV80CME 1B-WC/ GMEV80CMC 1B-WC/ GMEV80CMX 1B-WC	Green Motion EV Charger	AC	19.2	✓	⚠	
Espen	TSEA240V/48 AUS	TSEA240V/##AUS	AC	11.5	✓	✓	Single port.
Espen	TSEA240V/80 AUS	TSEA240V/##AUS	AC	19.2	✓	✓	Single port.
Espen	EVC/A48X2	EVC/A48X2	AC	11.5	✓	✓	Dual port.
EVGateway	EGW-#C-40-#		AC	9.6	✓	⚠	
EVGateway	EGW-#C-48-#		AC	11.5	✓	⚠	
EVGateway	EGW-EX-1193-#		AC	19.2	✓	⚠	
EVmode	EVM2000-EVM101U	EVM2000	AC	11.5	✓	✗	Single port.

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
EVSE LLC	3703	ChargeWorks EV Charger	AC	9.6	✓	⚠	Single port, Must acquire Gateway for network connectivity
EVSE LLC	3722	EVSE Garage Overhead Charger	AC	9.6	✓	⚠	Single port, Must acquire Gateway for network connectivity
EVSE LLC	3704 REV G	AutoCoil EV Charger	AC	9.6	✓	⚠	Single port, Must acquire Gateway for network connectivity
EVSE LLC	3704-002 REV G	AutoCoil EV Charger	AC	9.6	✓	⚠	Single port, Must acquire Gateway for network connectivity
Ford Pro Charging	FPC-AC0080ZC-U##	Ford Pro AC Charging Station, Series 2	AC	19.2	✓	✗	Single Port NRTL Listed as EX-1193-1
Free2Move	E21CA180Dx	48A Charger	AC	11	✓	✓	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Free2Move	E21CH012##		AC	11	✓	✓	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Free2Move	E21CH019Dx	80A Charger	AC	19.1	✓	✓	Single Port, Standalone network capability
ICAPIA	ICACLS4040	i4040	AC	9.6	✓	✓	Dual port.
ICAPIA	ICACLS4080	i4080	AC	19.2	✓	✓	Dual port.
ICAPIA	ICACLS80	i80	AC	19.2	✓	✓	Single port.
ICAPIA	ICACOP48	OPAL OMNI 48	AC	11.5	✓	✓	Single port.
InCharge	EX-1193-1		AC	19.2	✓	✗	Single Port NRTL Listed as EX-1193-1

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
InCharge	ICE 80A Dual	ICE 80A Dual	AC	19.2	✓	✗	Dual port.
Integra Energy	IEV-EVC/A40/R2	IEV-EVC/A40/R2	AC	9.6	✓	✓	Single port.
Integra Energy	IEV-EVC/A48/R2	IEV-EVC/A48/R2	AC	11.5	✓	✓	Single port.
IoTecha	CCS-ACL2 / CCS-C80A	CCS-C80A-xyyyy	AC	19.2	✓	✗	Single Port. xx - cable length (15 or 25ft) yyy - LTE option
IoTecha	CCS-C80C	CCS-C80C-xyyyy	AC	19.2	✓	✗	Single Port. xx - cable length (15 or 25ft) yyy - LTE option
IXP, LLC	IXP-E48	IXP-E48	AC	11.5	✓	✗	
IXP, LLC	IXP-E80	IXP-E80	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, 4G Module, ISO 15118 compliant, Credit Card Reader, Commercial, Gen 2, Orange
LEDVANCE LLC	75899	EVC/48A/LVL2/C2/OR	AC	11.5	✓	✗	EV Charger, 48 Amp, Level 2, Commercial, Gen 2, Orange
LEDVANCE LLC	75905	EVC/48A/LVL2/4G/C2/OR	AC	11.5	✓	✗	EV Charger, 48Amp, Level 2, 4G Module, Commercial, Gen 2, Orange
LEDVANCE LLC	75900	EVC/48A/LVL2/ISO/C2/OR	AC	11.5	✓	✗	EV Charger, 48 Amp, Level 2, ISO 15118 compliant, Commercial, Gen 2, Orange
LEDVANCE LLC	75906	EVC/48A/LVL2/4G/ISO/C2/OR	AC	11.5	✓	✗	EV Charger, 48 Amp, Level 2, 4G Module, ISO 15118 compliant, Commercial, Gen 2, Orange
LEDVANCE LLC	75901	EVC/48A/LVL2/ISO/CC/C2/OR	AC	11.5	✓	✗	EV Charger, 48 Amp, Level 2, ISO 15118 compliant, Credit Card Reader, Commercial, Gen 2, Orange
LEDVANCE LLC	75927	EVC/48A/LVL2/4G/CC/C2/OR	AC	11.5	✓	✗	EV Charger, 48 Amp, Level 2, 4G Module, Credit Card Reader, Commercial, Gen 2, Orange

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
LEDVANCE LLC	75907	EVC/48A/LVL2/4G/ISO/CC/C2/OR	AC	11.5	✓	✗	EV Charger, 48 Amp, Level 2, 4G Module, ISO 15118 compliant, Credit Card Reader, Commercial, Gen 2, Orange
LEDVANCE LLC	75902	EVC/80A/LVL2/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, Commercial, Gen 2, Orange
LEDVANCE LLC	75915	EVC/80A/LVL2/4G/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, 4G Module, Commercial, Gen 2, Orange
LEDVANCE LLC	74903	EVC/80A/LVL2/ISO/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, ISO 15118 compliant, Commercial, Gen 2, Orange
LEDVANCE LLC	75925	EVC/80A/LVL2/4G/ISO/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, 4G Module, ISO 15118 compliant, Commercial, Gen 2, Orange
LEDVANCE LLC	75904	EVC/80A/LVL2/ISO/CC/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, ISO 15118 compliant, Credit Card Reader, Commercial, Gen 2, Orange
LEDVANCE LLC	75928	EVC/80A/LVL2/4G/CC/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, 4G Module, Credit Card Reader, Commercial, Gen 2, Orange
LEDVANCE LLC	75926	EVC/80A/LVL2/4G/ISO/CC/C2/OR	AC	19.2	✓	✗	EV Charger, 80 Amp, Level 2, 4G Module, ISO 15118 compliant, Credit Card Reader, Commercial, Gen 2, Orange
LongHorn	ECA-NC8002S-DG40***		AC	9.6	✓	✓	Dual port.
LongHorn	ECA-NC8002S-DG80***		AC	19.2	✓	✓	Dual port.
LongHorn	ECA-NC8002S-SG80***		AC	19.2	✓	✓	Single port.
Loop Global	EVS-40A-L2-001	EV Flex +	AC	9.6	✓	⚠	SAE J1772, Standalone network capability
Loop Global	EVS-80A-L2-001	EV-Fleet	AC	19.2	✓	⚠	SAE J1772, Standalone network capability
Loop Global	EVS-80A-L2-002	EV-Fleet	AC	19.2	✓	⚠	SAE J1772, Standalone network capability
Lynkwell	LW141-AC50	LW141-AC50	AC	12	✓	⚠	Single Port ; OCPP Full Certificate with software version V1.13.97
Lynkwell	LW141-AC80	LW141-AC80	AC	19.2	✓	✗	Single port.
Newtech	ECA-NC8002S-DG40-CJ10		AC	9.6	✓	✓	Dual port.
Newtech	ECA-NC8002S-DG80-CJ10		AC	19.2	✓	✓	Dual port.
Newtech	ECA-NC8002S-SG80-CJ10		AC	19.2	✓	✓	Single port.

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
Noodoe	AC11P/ AC11P Exceed		AC	11.5	✓	⚠	Single port.
OpConnect	IC80	IC80	AC	19.2	✓	✗	Single Port NRTL Listed as EX-1193-1
OpConnect	SC80	SC80	AC	19.2	✓	✗	Single Port NRTL Listed as EX-1193-3
PowerPump	AC5500	AC5500	AC	10	✓	✓	Single Port.
PowerPump	ACC550-C-40	ACC550-C-40	AC	9.6	✓	✓	Single port.
PowerPump	ACC550-C-48	ACC550-C-48	AC	11.5	✓	✓	Single port.
PowerPump	ACC550-C-80	ACC550-C-80	AC	19.2	✓	✓	Single port.
PowerPump	ACL22100-G40	ACL22100-G40	AC	9.6	✓	✓	Dual port.

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
PowerPump	ACL22100-G48	ACL22100-G48	AC	11.5	✓	✓	Dual port.
PowerPump	ACL22100-G80	ACL22100-G80	AC	19.2	✓	✓	Dual port.
QCharge123	QAC2-BC	Commercial Charger	AC	19.2	✓	✓	Single or dual port.
QCharge123	QAC2-BR	Residential/Low Commercial Charger	AC	9.6	✓	✓	Single port.
SWTCH Energy	EVM005 - Dual EV Charger	EVM005	AC	23	✓	✓	Dual port. 2x11.5kW ports
SWTCH Energy	EVM002-48	EVM002-48	AC	11.5	✓	✓	Single port
SWTCH Energy	EVM002-80	EVM002-80	AC	19.2	✓	✓	Single port
SWTCH Energy	AXLU111001/48	AX48	AC	11	✓	✓	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
SWTCH Energy	AXLU191001/80	AX80	AC	19.1	✓	✓	Single Port, Standalone network capability

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
SWTCH Energy	EX-1193-1	SWTCH Lite-On Platinum IC3 80A	AC	19.2	✓	✓	Single Port NRTL Listed as EX-1193-1
SWTCH Energy	EX-1193-3	SWTCH Lite-On Platinum SC3 80A	AC	19.2	✓	✓	Single Port NRTL Listed as EX-1193-3
SWTCH Energy	EVH006-48	Joint Tech 48A	AC	11.5	✓	✓	Single port.
TurnOnGreen	EVP1100-W/CPEVAC-11KW-J17-W EVP1100-WG/CPEVAC-11KW-J17-WG CPEVAC-11KW-S18-#		AC	11.4	✓	⚠	Single Port
Voltpost, Inc.	Voltpost Air Pole Mount	Voltpost Air	AC	9.6	✓	⚠	Single port, Must acquire Gateway for network connectivity
Xeal	A30L-25J1-5	Xeal Pro E - J1772 (WiFi)	AC	11.5	✓	✗	Single port.
Xeal	A30L-25J3-5	Xeal Pro E - NACS (WiFi)	AC	11.5	✗	✓	Single port.
Xeal	A31L-25J1-8	Xeal Max E - J1772 (Cell/WiFi)	AC	19.2	✓	✗	Single port.
Xeal	A31L-25J3-8	Xeal Max E - NACS (Cell/WiFi)	AC	11.5	✗	✓	Single port.
Xiamen Topstar Co., LTD	TSEA240V/40 AUS	TSEA240V/##AUS	AC	9.6	✓	✓	Single port.
Xiamen Topstar Co., LTD	TSEA240V/48 AUS	TSEA240V/##AUS	AC	11.5	✓	✓	Single port.
Xiamen Topstar Co., LTD	TSEA240V/80 AUS	TSEA240V/##AUS	AC	19.2	✓	✓	Single port.
Xiamen Topstar Co., LTD	TSED240V/40 A2US	TSED240V/##A2US	AC	9.6	✓	✓	Dual port.
Xiamen Topstar Co., LTD	TSED240V/48 A2US	TSED240V/##A2US	AC	11.5	✓	✓	Dual port.

AC Charging Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	J1772	J3400	Notes
Xiamen Topstar Co., LTD	TSED240V/80A2US	TSED240V/##A2US	AC	19.2	✓	✓	Dual port.
Zerova	AXLU111001/AX48	AX48	AC	11	✓	✓	Single Port, Standalone network capability; OCA Full and Security certificates under software version V1.00
Zerova	AXLU191001/AX80	AX80	AC	19.1	✓	✓	Single Port, Standalone network capability

Oregon Department of Transportation - Approved Product List

These Chargers and Networks meet the program requirements established by Oregon Department of Transportation for Round 5 of the Community Charging Rebate (CCR) program.

All equipment must:

- Be new and installed for the first time. Previously installed or rebuilt equipment is ineligible. Replacement of broken equipment is eligible, but projects must still follow the minimum port requirements.
- Be purchased and not leased.
- **Have a minimum two-year warranty**, either from the manufacturer, a third party, or the contractor. ODOT strongly encourages extended warranties.

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
ABB	C50S#NA###	C50	DC	50	Dual port.
Alpitronic	HYC400-1	Hypercharger	DC	100	1-4 Ports
Alpitronic	HYC400-2	Hypercharger	DC	200	1-4 Ports
Alpitronic	HYC400-3	Hypercharger	DC	300	1-4 Ports
Alpitronic	HYC400-4	Hypercharger	DC	400	1-4 Ports
Alpitronic	HYC50	Hypercharger	DC	50	1-2 Ports
Autel	DC Compact - UW040A2501	DC Compact	DC	40	Dual Port.
Autel	DC HiPower	DC HiPower	DC	640	set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Autel	MaxiCharger DH300	MaxiCharger DH300	DC	300	Dual or quad port.
Autel	MaxiCharger DH360	MaxiCharger DH360	DC	360	Dual or quad port.
Autel	MaxiCharger DH400	MaxiCharger DH400	DC	400	Dual or quad port.
Autel	MaxiCharger DH480	MaxiCharger DH480	DC	480	Dual or quad port.
Autel	UF060A3001	Maxicharger DC Fast 60kW	DC	60	Single or dual port

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Autel	UF080A3001	Maxicharger DC Fast 80kW	DC	80	Single or dual port
Autel	UF100A3001	Maxicharger DC Fast 100kW	DC	100	Single or dual port
Autel	UF120A3001	Maxicharger DC Fast 120kW	DC	120	Single or dual port
Autel	UF140A4001	Maxicharger DC Fast 140kW	DC	140	Single or dual port
Autel	UF160A4001	Maxicharger DC Fast 160kW	DC	160	Single or dual port
Autel	UF180A4001	Maxicharger DC Fast 180kW	DC	180	Single or dual port
Autel	UF200A4001	Maxicharger DC Fast 200kW	DC	200	Single or dual port
Autel	UF220A4001	Maxicharger DC Fast 220kW	DC	220	Single or dual port
Autel	UF240A4001	Maxicharger DC Fast 240kW	DC	240	Single or dual port
Blink	200-002334-A	Blink-SIN 120	DC	120	Dual port
Blink	200-002339-A	Blink-SIN 160	DC	160	Single port
Blink	200-002344-A	Blink-SIN 240	DC	240	Dual port
Blink	01-0581	Blink 240kW	DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0568	Blink 300kW	DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	01-0569	Blink 360kW	DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Blink	01-0578	Blink 180kW	DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	200-000320-A	Blink 200kW	DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Blink	C50##### C80#####	C-Series	DC	600	Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser outputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
breezEV	BEV-L3-D60		DC	60	Single or dual port
breezEV	BEV-L3-D120		DC	120	Single or dual port
BTC Power	HPCD8-350-0#	Fleet Dispenser	DC	180	Can power up to 4 dual port Fleet Dispensers to 1 Power Cabinet and charge sequentially. can charge up to 8 vehicles sequentially as a result.
BTC Power	HPCD6-500-05-005		DC	360	Can power up to 4 dual port Fleet Dispensers to 1 Power Cabinet and charge sequentially. can charge up to 8 vehicles sequentially as a result.
BTC Power	HPCT2-360-480-#		DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
BTC Power	HPCD7-350-###-01#	Gen4 Public Dispenser	DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
BTC Power	HPCT3-###-480-# / HPCD7-500-###-01#	Gen4 Public Dispenser	DC	360	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
BTC Power	L3A-180-480-###	Gen4 180kW AIO	DC	180	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
BTC Power	L3A-240-480-###	Gen4 240kW AIO	DC	240	BTC Power Hardware is network/backend agnostic, but also provide our own basic network option if needed
CENNTRO	DCC190C190	DC Electric Vehicle Charging Station	DC	180	Dual port.
CHAEVI	CV-3FD120P-IUL3	SONIC (120kW) (3 Phase, 3 Wire)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL3	SONIC (150kW) (3 Phase, 3 Wire)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
CHAEVI	CV-3FD180P-IUL3	SONIC (180kW) (3 Phase, 3 Wire)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD120P-IUL	SONIC (120kW) (3 Phase, 4 Wire)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD150P-IUL	SONIC (150kW) (3 Phase, 4 Wire)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3FD180P-IUL	SONIC (180kW) (3 Phase, 4 Wire)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available. NACS Cable Adaptable
CHAEVI	CV-3UD403P-NCC3 (CCS1/CCS1)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	CV-3UD403P-NCN3 (CCS1/NACS)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
CHAEVI	DCV-3FD120-ICN	DUOCONIC (120kW)	DC	120	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD150-ICN	DUOCONIC (150kW)	DC	150	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	DCV-3FD180-ICN	DUOCONIC (180kW)	DC	180	Dual port. Stand-Alone Equipment 120,150,180kW Serial-UL listed. Dynamic Load Balancing Available
CHAEVI	CV-3UD403P-NDN3 (NACS/NACS)	SUPERSONIC	DC	400	All-in-One Equipment - UL, CTEP listed - Dynamic Load Balancing Available - CCS/NACS Cable
Charge America	MCS1200	MCS 4x16 Power Cabinet	DC	1200	Allows 5 CCS connector as well as de-rated configuration with 1, 2, ... 5 CCS ports
ChargePoint	CPE250C-625-CCS1-200A-****	Express 250	DC	62.5	ChargePoint Express 250 Station (62.5 kW) - includes Express 250 Station, 2x Power Modules, 1x CCS1 200A cable, 1x CHAdeMO cable or NACS, North America Modem/SIM, cUL and UL listed, requires CPE250-CMT-IMPERIAL in US, CPE250-CMT-METRIC in Canada. CPE250-CMT-IMPERIAL/METRIC not included. FWHA and FTA compliant models available as well as with integrated EMV Chip Reader terminal.
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DC	160	[Paired Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
ChargePoint	CPE280-800-NA	Express 280 DC Fast Charging Station	DC	80	[Single Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-CHIP	Express 280 DC Fast Charging Station	DC	80	[Single Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	CPE280-800-NA-FHWA	Express 280 DC Fast Charging Station	DC	80	[Single Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
ChargePoint	Express Plus 1000 Power Block: CPPB0001*** PM1.5 43-001200-** EXPP-PL10###*-*##*#-##*#*#-***	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 1000 series; Used for Fleet or Commercial.
ChargePoint	Express Plus 2000 (EXPP-PL20##-FHWA)	Express Plus	DC	500	[FHWA sku] Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO
ChargePoint	Express Plus 2000 (EXPP-PL20##)	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO
ChargeSmart EV	CSEV-DC060		DC	60	Single or dual port
ChargeSmart EV	CSEV-DC080		DC	80	Single or dual port
ChargeSmart EV	CSEV-DC100		DC	100	Single or dual port
ChargeSmart EV	CSEV-DC120		DC	120	Single or dual port
ChargeSmart EV	CSEV-DC140		DC	140	Single or dual port

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
ChargeSmart EV	CSEV-DC160		DC	160	Single or dual port
ChargeSmart EV	CSEV-DC180		DC	180	Single or dual port
ChargeSmart EV	CSEV-DC200		DC	200	Single or dual port
ChargeSmart EV	CSEV-DC220		DC	220	Single or dual port
ChargeSmart EV	CSEV-DC240		DC	240	Single or dual port
ChargeSmart EV	CSEV-DCHi		DC	640	The CSEV-DCHi has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
ChargeTronix	CTX-AiO-120	Apex 120kW DCFC	DC	120	Dual port.
ChargeTronix	CTX-AiO-160	Apex 160kW DCFC	DC	160	Dual port.
ChargeTronix	CTX-AiO-240	Apex 240kW DCFC	DC	240	Dual port.
ChargeTronix	CTX-AiO-60	Apex 60kW DCFC	DC	60	Dual port.
ChargeTronix	Power Cabinet: CTX-DSPB-360 Dispenser: CTX-DST	Nexus 360kW Distributed System	DC	360	Up to 6 ports.
ChargeTronix	Power Cabinet: CTX-DSPB-480 Dispenser: CTX-DST	Nexus 480kW Distributed System	DC	480	Up to 6 ports.
ChargeTronix	TP-EVPD-160kW	160kW DCFC	DC	160	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
ChargeTronix	TP-EVPD-180kW	180kW DCFC	DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
ChargeTronix	TP-EVPD-200kW	200kW	DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
ChargeTronix	TP-EVPD-240kW	240kW DCFC	DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
ChargeTronix	TP-EVPD-300kW	300kW DCFC	DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
ChargeTronix	TP-EVPD-360kW	360kW DCFC	DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
DynaChrg	EVN120P	Stand alone Advertising 120	DC	120	120kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 120 Flagship, DirectPowerPS 120

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
DynaChrg	EVN180P	Stand alone Advertising 180	DC	180	180kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 180 Flagship, DirectPowerPS 180
DynaChrg	EVN240P	Stand alone Advertising 240	DC	240	240kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 240 Flagship, DirectPowerPS 240
DynaChrg	EVN300P	Stand alone Advertising 300	DC	300	300kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 300 Flagship, DirectPowerPS 300
DynaChrg	EVN360P	Stand alone Advertising 360	DC	360	360kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 360 Flagship, DirectPowerPS 360
DynaChrg	EVS160	160kW Standalone Unit	DC	160	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
DynaChrg	EVS240	240kW Standalone Unit	DC	240	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
DynaChrg	EVS480	Distributed Model 480kW up to 3 Dual Port Dispensers	DC	480	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Air cooling output 350A Liquid cooling sustained maximum output 500A
Eaton	CPE250C-625-CCS1-200A- ****-ETN	Express 250	DC	62.5	ChargePoint Express 250 Station (62.5 kW) - includes Express 250 Station, 2x Power Modules, 1x CCS1 200A cable, 1x CHAdeMO cable or NACS, North America Modem/SIM, cUL and UL listed, requires CPE250-CMT-IMPERIAL in US, CPE250-CMT-METRIC in Canada. CPE250-CMT-IMPERIAL/METRIC not included. FWH and FTA compliant models available as well as with integrated EMV Chip Reader terminal.

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Eaton	CPE280-800-NA-CHIP-ETN	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
Eaton	CPE280-800-NA-CHIP-ETN	Express 280 DC Fast Charging Station	DC	80	[Single Unit, Credit Card Reader sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
Eaton	CPE280-800-NA-ETN	Express 280 DC Fast Charging Station	DC	160	[Paired Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
Eaton	CPE280-800-NA-ETN	Express 280 DC Fast Charging Station	DC	80	[Single Unit] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
Eaton	CPE280-800-NA-FHWA-ETN	Express 280 DC Fast Charging Station	DC	160	[Paired Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
Eaton	CPE280-800-NA-FHWA-ETN	Express 280 DC Fast Charging Station	DC	80	[Single Unit, FHWA sku] ChargePoint Express 280 Station (80 kW) - includes Express 280 Station, 2x Power Modules, 1 or 2 connectors including CCS1, CHAdeMO, NACS. North America Modem/SIM, cUL and UL listed, FWHA and FTA compliant models available.
Eaton	EXPP-PL20##-CHIP-ETN	Express Plus 2000	DC	500	[CHIP sku]Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO
Eaton	EXPP-PL20##-ETN	Express Plus 2000	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO
Eaton	EXPP-PL20##-FHWA-ETN	Express Plus 2000	DC	500	[FHWA sku] Express Plus system includes Power Block, Power Modules, and Power Link 2000 series; Each Power Link Dispenser can include 1 or 2 connector including CCS, NACS, or CHAdeMO

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Eaton	Express Plus 1000 Power Block: CPPB0001***-ETN PM1.5 43-001200-**-ETN EXPP-PL10##*-##*##-##*##-***-ETN	Express Plus	DC	500	Express Plus system includes Power Block, Power Modules, and Power Link 1000 series; Used for Fleet or Commercial.
Ekoenergetyka	AXE-S2A7-66XX4XXXX, AXE-S2A7-65XX4XXXX, AXE-S2A7-55, AXE-S2A7-56, AXE-S2A7-66, AXE-O2A7-55, AXE-O2A7-56, AXE-O2A7-66	Axon Easy 120	DC	120	Dual port.
Ekoenergetyka	AXE-S2B0-65XX4XXXX, AXE-S2B0-66XX4XXXX, AXE-S2B0-55, AXE-S2B0-56, AXE-S2B0-66, AXE-O2B0-55, AXE-O2B0-56, AXE-O2B0-66	Axon Easy 180	DC	180	Dual port.
Espen	EVC/D030/S####	EVC/D030/S####	DC	30	1x CCS1 connector 1x CHAdeMO connector
Espen	EVC/D060/S####	EVC/D060/S####	DC	60	1x CCS1 connector 1x CHAdeMO connector
Espen	EVC/D120/S####	EVC/D120/S####	DC	120	1x CCS1 connector 1x CHAdeMO connector
Espen	EVC/D180/S####	EVC/D180/S####	DC	180	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
EverCharge	E800-1042-01	DCFC 320kW All-in-One, w/ Dual CCS1	DC	320	Dual port.
EVPassport	C6AM150XX	C6AM150XX	DC	150	Standalone DCFC, no HPC needed, runs off its own power
EVPassport	C6AM90XX	C6AM90XX	DC	95	Runs on 208 3P power, standalone DCFC
EVSIS	JC-94F2-350-0T5	DC Charger 350kW	DC	350	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-94F2-400-0T5	DC Charger 400kW	DC	400	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-100-CT	DC Charger 100kW	DC	100	CCS/CHAdeMO (optional), OCPP 2.0.1 will be supported
EVSIS	JC-9932-180-CT	DC Charger 180kW	DC	180	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
EVSIS	JC-9932-240-CT	DC Charger 240kW	DC	240	Dual port. CCS / NACS(Optional), OCPP 2.0.1 will be supported
EVSIS	JC-9A31-30-CT	DC Charger 30kW	DC	30	CCS/OCPP 2.0.1 will be supported
FLO	Ultra	Ultra	DC	320	Dual port.
Free2Move	E21CH060Dx		DC	60	1x CCS1 connector 1x CHAdeMO connector
Free2Move	E21CH180##		DC	180	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Freewire	900-00151-XX	Boost 150	DC	150	Battery integrated DCFC
Freewire	Boost 200	Boost Charger 200	DC	200	1x CCS1 connector 1x CHAdeMO connector
Gateway International 360	GW-EV4040-60-XXX	GW-EV4040-60-XXX	DC	60	1x CCS1 connector 1x CHAdeMO connector
Gateway International 360	GW-EV3000/XXX	GW-EV3000/XXX	DC	30	1x CCS1 connector 1x CHAdeMO connector
Gateway International 360	GW-EV4400-120/XXX	GW-EV4400-120/XXX	DC	120	1x CCS1 connector 1x CHAdeMO connector
Gateway International 360	GW-EV4400-180/XXX	GW-EV4400-180/XXX	DC	180	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00
Gateway International 360	GW-EV4400-60/XXX	GW-EV4400-60/XXX	DC	60	1x CCS1 connector 1x CHAdeMO connector
Gravity	GR-LH500CX		DC	500	
Gravity	GT-AH200XX		DC	200	
Gravity	GT-AV200XX		DC	200	
Gravity	GT-LAV500EX		DC	500	
Gravity	GT-LLH500EX		DC	500	
Gravity	GT-LV500CX		DC	500	
i-charging	blueberry	BB50	DC	50	Dual port
i-charging	blueberry CLUSTER	blueberry CLUSTER	DC	500	Four ports. Simultaneous charging, Dynamic Power Allocation, 50 to 900 kW. 1 to 3 Power Units (cabinets) and up to 4 plugs in dispenser and satellites
i-charging	blueberry FUSION	blueberry FUSION	DC	150	Dual port. Simultaneous charging, Dynamic Power Allocation, 50, 100 and 150kW available
i-charging	blueberry PLUS	PU 200 R2 / PU 300 R2	DC	500	Four ports. Simultaneous charging, Dynamic Power Allocation, 50 to 900 kW. 1 to 3 Power Units (cabinets) and 1 Dispenser w 2 Plugs
ICAPIA	IDCFC-360AD-P-CC/CN/NN	IDCFC 360AD	DC	360	360kW single port use, 180kW dual port use
ICAPIA	IDCFC-240AD-P-CC/CN/NN	IDCFC 240AD	DC	240	240kW single port use, 120kW dual port use
ICAPIA	IDCFC-180AD-P-CC/CN/NN	IDCFC 180AD	DC	180	180kW single port use, 90kW dual port use

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
iENERGIE360 US INC. dba. Injet	iNSCDA120K1	Ampax	DC	120	Dual port.
iENERGIE360 US INC. dba. Injet	iNSCDA150K1	Ampax	DC	150	Dual port.
iENERGIE360 US INC. dba. Injet	iNSCDA180K1	Ampax	DC	180	Dual port.
iENERGIE360 US INC. dba. Injet	iNSCDA240K1	Ampax	DC	240	Dual port.
InCharge	ICE 480	ICE 480	DC	480	Supports both CCS and CHAdeMO standards with one or two connectors. This DC Split System is designed to provide high power charging with distributed dispenser and power conversion units.
InCharge	ICE CUBE 200kWh/200kW Battery Buffer	ICE CUBE 200kWh/200kW Battery Buffer	DC	240	Battery integrated DCFC. Up to 4 ports.
InCharge	ICE-120	ICE-120	DC	120	1x CCS1 connector 1x CHAdeMO connector NRTL listed as Shenzhen InfyPower : EXP120K2-FD-UU2 & EXP120K2-FS-U2
InCharge	ICE-180	ICE-180	DC	180	1x CCS1 connector 1x CHAdeMO connector NRTL listed as Shenzhen InfyPower : EXP180K2-FD-UU2 & EXP180K2-FS-U2
InCharge	ICE-30	ICE-30	DC	30	1x CCS1 connector 1x CHAdeMO connector NRTL listed as Shenzhen InfyPower : EXP30k2-FSW-U2 & EXP30kW-FDW-UU2
InCharge	ICE-60	ICE-60	DC	60	1x CCS1 connector 1x CHAdeMO connector NRTL listed as Shenzhen InfyPower : EXP60K2-FD-UU2 & EXP60K2-FS-U2
InCharge	ICE60K3-FDW-UU2	ICE-60 DCWB	DC	60	Dual port.
InCharge	IDC600K3-FMR5-2	ICE-600	DC	600	Ten ports.
Ingeteam	RAPID 120	RAPID 120	DC	120	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 150	RAPID 150	DC	150	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 180	RAPID 180	DC	180	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 60E	RAPID 60E	DC	60	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Ingeteam	RAPID 90	RAPID 90	DC	90	Stand-alone. Single or dual port. CCS1, NACS and/or CHAdeMO.
Integra Energy	IEV/D030/SXXX	IEV/D030/SXXX	DC	30	1x CCS1 connector 1x CHAdeMO connector
Integra Energy	IEV/D060/SXXX	IEV/D060/SXXX	DC	60	1x CCS1 connector 1x CHAdeMO connector
Integra Energy	IEV/D120/SXXX	IEV/D120/SXXX	DC	120	1x CCS1 connector 1x CHAdeMO connector
Integra Energy	IEV/D180/SXXX	IEV/D180/SXXX	DC	180	1x CCS1 connector 1x CHAdeMO connector; OCA Full and Security certificates under software version V1.00

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Jule (eCAMION)	Jule-100	Jule Charger 100	DC	100	DCFC that works with ESS w/ voltage range 650-800VDC
Jule (eCAMION)	Jule-200	Jule Charger 200	DC	200	DCFC that works with ESS w/ voltage range 650-800VDC
Jule (eCAMION)	Jule-350	Jule Charger 350	DC	350	DCFC that works with ESS w/ voltage range 650-800VDC
Kempower	SMS2K5MSLV1	MEGA Satellite Flex MCS/CCS1	DC	1200	Only one port active at a time. Must be combined with a Kempower Power Unit
Kempower	SMT2K5MSLV1	MEGA Satellite Flex MCS/NACS	DC	1200	Only one port active at a time. Must be combined with a Kempower Power Unit
Kempower	C50##### C80#####	C-Series (Single)	DC	600	(Single) Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser outputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
Kempower	C50##### C80#####	C-Series (Paired)	DC	1200	(Paired) Up to 8 ports. Kempower Power Unit supplies DC power to various distributed dispenser outputs including but not limited to the Kempower Satellite (offers single or dual port configurations), the Kempower Liquid Cooled Satellite, etc.. Details about qualifications relevant to each variant is detailed in the corresponding notes section.
Kempower	C501###	C-Series	DC	200	1-4 power modules supporting max output range of 50-200kW
Kempower	C502###	C-Series	DC	350	1-7 power modules supporting max output range of 50-350kW
Kempower	C503###	C-Series	DC	350	1-7 power modules supporting max output range of 50-350kW
Kempower	C801###	C-Series	DC	200	1-4 power modules supporting max output range of 50-200kW
Kempower	C802###	C-Series	DC	350	1-7 power modules supporting max output range of 50-350kW
Kempower	C803###	C-Series	DC	350	1-7 power modules supporting max output range of 50-350kW
Loop Global	EVS-FLASH-300-D01	Infinity Flash (with screen)	DC	300	Dual port with screen. Power cabinet required: EVS-FLASH- 360-PC01
Loop Global	EVS-FLASH-300-D01-150	Infinity Flash (with screen)(derated)	DC	150	150kW max per port
Loop Global	EVS-FLASH-300-D02	Infinity Flash (without screen)	DC	300	Dual port without screen. Power cabinet required: EVS-FLASH- 360-PC01
Loop Global	EVS-FLASH-300-D02-150	Infinity Flash (without screen)(derated)	DC	150	150kW max per port
Lynkwell	LW141-DC480/480-SA-CC18	LW141-DC480/480-SA-CC18	DC	480	Dual port. 2x CCS1 connector
Lynkwell	LW141-DC480/480-SA-CN-18	LW141-DC480/480-SA-CN-18	DC	480	Dual port. 1x CCS1 connector, 1x NACS/J3400 connector
Lynkwell	LW141-DC480/400-SA-CC18	LW141-DC480/400-SA-CC18	DC	400	Dual port. 2x CCS1 connector
Lynkwell	LW141-DC480/400-SA-CN18	LW141-DC480/400-SA-CN18	DC	400	Dual port. 1x CCS1 connector, 1x NACS/J3400 connector
Lynkwell	LW141-DC480/320-SA-CC18	LW141-DC480/320-SA-CC18	DC	320	Dual port. 2x CCS1 connector

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Lynkwell	LW141-DC480/320-SA-CN18	LW141-DC480/320-SA-CN18	DC	320	Dual port. 1x CCS1 connector, 1x NACS/J3400 connector
Lynkwell	LW141-DC100	LW141-DC100	DC	100	Single or dual port
Lynkwell	LW141-DC120	LW141-DC120	DC	120	Single or dual port
Lynkwell	LW141-DC140	LW141-DC140	DC	140	Single or dual port
Lynkwell	LW141-DC160	LW141-DC160	DC	160	Single or dual port
Lynkwell	LW141-DC180	LW141-DC180	DC	180	Single or dual port
Lynkwell	LW141-DC200	LW141-DC200	DC	200	Single or dual port
Lynkwell	LW141-DC220	LW141-DC220	DC	220	Single or dual port
Lynkwell	LW141-DC240	LW141-DC240	DC	240	Single or dual port
Lynkwell	LW141-DC60	LW141-DC60	DC	60	Single or dual port
Lynkwell	LW141-DC640	LW141-DC640	DC	640	The DC HiPower has a power cabinet with dispenser set up. It comes in 320, 480, or 640kW options and can be purchased with 2, 4, 6, or 8 ports depending on the number of dispensers.
Lynkwell	LW141-DC80	LW141-DC80	DC	80	Single or dual port
Lynkwell	LW301-DC320	LW301-DC320	DC	320	Dual port.
Nidec	EVDIS-L120DAWM010	DirectPowerPS Tower 120 Flagship	DC	120	120kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 120 Flagship, DirectPowerPS 120
Nidec	EVDIS-L180DAWM010	DirectPowerPS Tower 180 Flagship	DC	180	180kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 180 Flagship, DirectPowerPS 180
Nidec	EVDIS-L240DAWM000	DirectPowerPS Tower 240 Flagship	DC	240	240kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 240 Flagship, DirectPowerPS 240
Nidec	EVDIS-L300DAWM000	DirectPowerPS Tower 300 Flagship	DC	300	300kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 300 Flagship, DirectPowerPS 300
Nidec	EVDIS-L360DAWM000	DirectPowerPS Tower 360 Flagship	DC	360	360kW all-in-one charger with 2 connectors, advertising display, and payment terminal. Alternate designations: DirectPowerPS 360 Flagship, DirectPowerPS 360
Nuvve	TP-160DC-V1G(-####)	EVSE Nuvve DCFC 160kW Smart Charging Station (Single or Dual Port, CCS1 or NACS, Power Sharing, non-BABA or BABA)	DC	160	Dual port. Can be configured with: 2x CCS, 2x NACS, 2x CHAdeMO, 1x CCS + 1x NACS, 1x CCS + 1x CHAdeMO
Nuvve	TP-180DC-V1G(-####)	EVSE Nuvve DCFC 180kW Smart Charging Station (Single or Dual Port, CCS1 or NACS, Power Sharing, non-BABA or BABA)	DC	180	Dual port. Can be configured with: 2x CCS, 2x NACS, 2x CHAdeMO, 1x CCS + 1x NACS, 1x CCS + 1x CHAdeMO
Nuvve	TP-200DC-V1G(-####)	EVSE Nuvve DCFC 200kW Smart Charging Station (Single or Dual Port, CCS1 or NACS, Power Sharing, non-BABA or BABA)	DC	200	Dual Port, either 2x CCS or 1x CCS + 1x CHAdeMO

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Nuvve	TP-240DC-V1G(-####)	EVSE Nuvve DCFC 240kW Smart Charging Station (Single or Dual Port, CCS1 or NACS, Power Sharing, non-BABA or BABA)	DC	240	Dual Port, either 2x CCS or 1x CCS + 1x CHAdeMO
Nuvve	TP-300HPDC-V1G(-####)	EVSE Nuvve DCFC 300kW Smart Charging Station (Single or Dual Port, CCS1 or NACS, Power Sharing, non-BABA or BABA)	DC	300	Dual Port, either 2x CCS or 1x CCS + 1x CHAdeMO
Nuvve	TP-360HPDC-V1G(-####)	EVSE Nuvve DCFC 360kW Smart Charging Station (Single or Dual Port, CCS1 or NACS, Power Sharing, non-BABA or BABA)	DC	360	Dual Port, either 2x CCS or 1x CCS + 1x CHAdeMO
Power Electronics	NB240U	NB400	DC	240	Dual port.
Power Electronics	NB320U	NB400	DC	320	Dual port.
Power Electronics	NB400U	NB400	DC	400	Dual port.
QualCharge	SEC1000/60Y		DC	60	Dual port
QualCharge	SEC1000/120Y		DC	120	Dual port
QualCharge	SEC1000/160Y		DC	160	Single port
QualCharge	SEC1000/240Y		DC	240	Dual port
QualCharge	SEC1000/360F-N-U		DC	360	Up to 6 ports
QualCharge	SEC1000/480F-N-U		DC	480	Up to 6 ports
QualCharge	SEC1000/300U		DC	400	Dual port
QualCharge	SEC1000/500U		DC	480	Dual port
Rivian	PT01359256-B	RAN 1.5 CCS	DC	300	The standard configuration is a single-port charger with a CCS1 connector, rated at 300 kW. Alternatively, the charger can be configured as a dual-port split system. In this setup, two single-port dispensers are installed, each connected to the same power cabinet, resulting in a maximum power output of 150 kW per port.

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
Sinexcel	SEC1000/160Y-H-U ; SEC1000/160Y-T-U ; SEC1000/160Y-HH-U ; SEC1000/160Y-TT-U ; SEC1000/160Y-HT-U ; SEC1000/120Y-H-U ; SEC1000/120Y-T-U ; SEC1000/120Y-HH-U ; SEC1000/120Y-TT-U ; SEC1000/120Y-HT-U ; SEC1000/60Y-C-U ; SEC1000/60Y-S-U ; SEC1000/60Y-CC-U ; SEC1000/60Y-SS-U ; SEC1000/60Y-SC-U ;	SEC160	DC	160	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/240Y-H-U SEC1000/240Y-HH-U SEC1000/240Y-HJ-U SEC1000/240Y-T-U SEC1000/240Y-HT-U SEC1000/240Y-TJ-U SEC1000/240Y-TT-U	SEC 240	DC	240	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Can Output 350A CCS1 boost 500A NACS boost 400A
Sinexcel	SEC1000/360F-N-U SEC1000/480F-N-U SEC1000/200U-C-U SEC1000/200U-CC-U SEC1000/200U-CJ-U SEC1000/300U-H-U SEC1000/300U-HH-U SEC1000/300U-HC-U SEC1000/300U-HJ-U SEC1000/500U-F-U SEC1000/500U-FH-U SEC1000/500U-FC-U SEC1000/500U-FJ-U SEC1000/300U-T-U SEC1000/300U-TJ-U SEC1000/300U-HT-U SEC1000/300U-TT-U SEC1000/300U-TC-U SEC1000/500U-FT-U	SEC 480	DC	480	Output range:200V-1000V efficiency:Up to 96% Full certification User-friendly ADA Multiple payment methods Support for customization PLUG& CHARGE Hardware 15118-Ready Air cooling output 350A Liquid cooling sustained maximum output 500A
StarCharge	DC####AN238XY (####: 1600, 1200, 0800, 0600)	Oberon	DC	160	Dual port.
StarCharge	DC####AN147XYZ (####: 3200, 2800, 2400, 1800, 1500, 1200)	Titan V4	DC	320	Dual port.
StarCharge	Dispenser: DC7600AN171XY, Power Cabinet: DC7200AN153006	Aries V2 & Nova 720	DC	720	2 -12 ports

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
StarCharge	DC3200AN147XYZ/ DC2800AN147XYZ/ DC2400AN147XYZ/ DC1800AN147XYZ/ DC1500AN147XYZ/ DC1200AN147XYZ	Titan 320kW	DC	320	Dual port.
TECO- Westinghouse	DSWU122	Nexe VersaCharge 180kW	DC	120	1x CCS1 connector 1x CHAdeMO connector
TECO- Westinghouse	DSWU182	Nexe VersaCharge 60kW	DC	180	1x CCS1 connector 1x CHAdeMO connector
TECO- Westinghouse	DSWU601	Nexe VersaCharge 90kW	DC	60	1x CCS1 connector 1x CHAdeMO connector
TECO- Westinghouse	DSWU901		DC	90	1x CCS1 connector 1x CHAdeMO connector
TECO- Westinghouse	DWWU301/ DW30		DC	30	1x CCS1 connector 1x CHAdeMO connector
Tellus Power	TP-EVPD-160kW (TP5-160-480)		DC	160	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Tellus Power	TP-EVPD-180kW (TP5-180-480)		DC	180	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Tellus Power	TP-EVPD-200kW (TP5-200-480)		DC	200	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Tellus Power	TP-EVPD-240kW (TP5-240-480)		DC	240	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Tellus Power	TP-EVPD-300kW (TP5-300-480)		DC	300	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Tellus Power	TP-EVPD-360kW (TP5-360-480)		DC	360	Dual Port ; either 2 x CCS or 1x CCS + 1x CHAdeMO or or 1x CCS + 1x NACS or 2 x NACS
Tesla	2424242-XX-Y	Supercharger V4 Cabinet	DC	1200	Up to 8 ports.
Tesla	1450758	SuperCharger V3 Cabinet	DC	387	Up to 4 ports
Tesla	1732843	SuperCharger V4 Post	DC	250	Single port
Tritium	PKM150		DC	150	Charging station is DC-fed
Tritium	TRI-153-RTM-02-025-####	RTM 25	DC	25	1x CCS1 connector 1x CHAdeMO connector
Tritium	TRI-153-RTM-02-050-####	RTM 50	DC	50	1x CCS1 connector 1x CHAdeMO connector
Tritium	TRI-153-RTM-02-075-####	RTM 75	DC	75	1x CCS1 connector 1x CHAdeMO connector
TurnOnGreen	FSP1200/CPEVDC-120KW-#	FSP1200	DC	120	Single Port, CCS connector
TurnOnGreen	FSP300/CPEVDC-30KW-#	FSP300	DC	30	Single Port, CCS connector
TurnOnGreen	FSP600/CPEVDC-60KW-#	FSP600	DC	60	Single Port, CCS connector
XCharge	C6AM150XX	C6AM150XX	DC	150	Standalone DCFC, no HPC needed, runs off its own power

DCFC Equipment

Brand	Model Number	Model Name	Type	Max Power (kW)	Notes
XCharge	C6AM200XX (125kW)	C6AM200XX (125kW)	DC	125	Runs on 208 3P power, standalone DCFC
XCharge	C6AM90XX	C6AM90XX	DC	95	Runs on 208 3P power, standalone DCFC
Xcharge	C7AM-240-CC / C7AM-240-LQ-CC	C7AM	DC	240	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
Xcharge	C7AM-280-CC / C7AM-280-LQ-CC	C7AM	DC	280	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
Xcharge	C7AM-320-CC / C7AM-320-LQ-CC	C7AM	DC	320	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
Xcharge	C7AM-360-CC / C7AM-360-LQ-CC	C7AM	DC	360	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
Xcharge	C7AM-400-CC / C7AM-400-LQ-CC	C7AM	DC	400	Dual port DCFC (up to 400kW), available with both CCS1 and NACS (liquid or air cooled cable)
XCharge	NZS/215, NZS/430	GridLink 01, GridLink 02	DC	300	All-in-one battery-integrated storage system delivering dual-port DC fast charging up to 300kW with CCS1 and NACS, requiring minimal grid power for flexible, high-performance deployment
Zerova	DQ480: DQWU482/DQWA482	DQ Series: DQ480	DC	480	Configurable to four or two cables
Zerova	DQWA242	DQ240	DC	240	Configurable to four or two cables
Zerova	DQWA360	DQ360	DC	360	Configurable to four or two cables
Zerova	DS120: DSWU122/DSWA122	DS Series: DS120	DC	120	Configurable to four or two cables
Zerova	DS150: DSWU152/DSWA152	DS Series: DS150	DC	150	Configurable to four or two cables
Zerova	DS180: DSWU182/DSWA182	DS Series: DS180	DC	180	Configurable to four or two cables
Zerova	DS60: DSWU601/DSWA601/SF##601	DS Series: DS60/SF60	DC	60	Configurable to four or two cables
Zerova	DS90: DSWU901/DSWA901	DS Series: DS90	DC	90	Configurable to four or two cables
Zerova	DT240: DTWA240	DT Series: DT240	DC	240	Configurable to four or two cables
Zerova	DW30: DWWU301/DWWA301	DW Series: DW30	DC	30	1x CCS1 connector 1x CHAdeMO connector
Zerova	DZ480: DZWU482/DEZW	DZ Series: DZ480	DC	480	Configurable to two, four, or six cables

Oregon Department of Transportation - Approved Product List

These Chargers and Networks meet the program requirements established by Oregon Department of Transportation for Round 5 of the Community Charging Rebate (CCR) program.

All equipment must:

- Be new and installed for the first time. Previously installed or rebuilt equipment is ineligible. Replacement of broken equipment is eligible, but projects must still follow the minimum port requirements.
- Be purchased and not leased.
- **Have a minimum two-year warranty**, either from the manufacturer, a third party, or the contractor. ODOT strongly encourages extended warranties.

Networks

Brand	Network	Notes
AMPECO	AMPECO Charge	
AmpUp	AmpUp	
Autel	Autel Cloud	OCPP Full certificate for software version 2.0.105
Blink	Blink Network	
BreatheEV	BreatheEV	
CHAEVI	CHAEVI	
Charge America	Charge America Network	
ChargePoint	ChargePoint Network	
Chargie	Chargie Network	
Charli Charging	Charli Charging	
DynaChrg	DynaChrg	
Eaton	Eaton Network	
Electric Avenue	Electric Avenue	

Networks

Brand	Network	Notes
Electrify America	Electrify America	
Epic Charging	Epic Charging	
EV Connect	EVConnect	
EV Plus	EV+ Charging	
Gravity	Gravity Network	
ICAPIA	ICAPIA	
LEOTEK	LEOTEK	
Noodoe		OCPP Full certificate for software version v1.0.2
OpConnect	OpConnect Network	
OPF Energy, LLC	OPF Energy, LLC	
PowerPump	PowerPump	
SWTCH Energy	SWTCH	
SynergEV	SynergEV	
The Mobility House	ChargePilot	
Wevo Energy	Wevo Energy	

Networks

Brand	Network	Notes
Xeal	Xeal Network	
ZGO Charge LLC	ZGo Charge LLC	