Form 6-54

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator REICHHOLD ENERGY CORPORATION Field Mist

Well No. Adams 34-28 , Sec. 28 , T. 7N R. 5W W.B. & M.

Signed Tim Williamson

Date 10-27-82 Title Drilling Superintendent

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date	
9-14-82	Mix mud and drilling 9 7/8" surface hole 449'
9-15-82	Completed surface hole @ 571', ran 516' 7" surface pipe and cemented same with 250 sxs class "G" cement containing 3% $CaCl_2$
9-16-82	Nippled up B.O.P.'s and tested with Dennis Olmstead witnessing. Drilled cement, guide shoe and 6 1/4 hole to 952'
9-17-82	Drilling 1744'
9-18-82	Drilling 2270'
9-19-82	Drilling 2561'
9-20-82	Drilled to 2572' Rigged up Schlumberger and logging
9-21-82	Waiting on orders
9-22-82	Rigged up Halliburton and pumped cement plug from 614'-330', 73 sxs class "G" containing 3% calcium chloride
9-23-82	Tagged plug and released rig 9-23-82