


APPLICATION FOR PERMIT TO DRILL NEW WELL OR STRATIGRAPHIC HOLE
(To be accompanied by a \$25.00 permit fee for new wells only and a surety bond conditioned as provided by law.)Canby Oregon May 25 19 60Department of Geology and Mineral Industries
Portland, Oregon

In compliance with rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) application is hereby made for permit to drill

a (new well) to be known as: Ross R. Mitchell & Associates Bliven
(stratigraphic hole) 2 in SE $\frac{1}{4}$ of Sec. 10, T. 8 S, R. 5 W W. B. & M.,
Well No. 2 in Dallas area Field, Polk County.Section of land
Area 640 acresThis well is 2255 feet ~~(N)~~ (S) of the north line and 2750 feet
~~(E)~~ (W) of the east line of section 10

(Give location from section or other legal subdivision lines or corners. Cross out wrong directions)

Elevation of ground above sea level is 400.4 feet. All depth measurements are taken from
top of derrick floor, which is + 3 feet above ground.The lessee is Ross Mitchell & AssociatesAddress P.O. Box 926, Canby, OregonThe lessor is Walter and Arthur BlivenLOCATE WELL CORRECTLY Address Route 3, Dallas, OregonWe estimate that the first productive oil or gas sand should occur at a depth of about 500 feet.
We propose to use the following strings of casing and to land or cement them as herein indicated:

Size of hole	Size of casing	Weight in pounds per foot	Grade and type	New or second hand	Depth	Landed or cemented No. sacks cement
10"	8"	25 pounds	Standard	Used	50'	15 sacks around shoe.
8"	5"	14 pounds	Standard	Used	500'	Cement if necessary.

We propose to drill with ~~rotary~~ rotary tools.

If changes in the above plan become advisable we will notify you before cementing or landing casing.

Additional information including names of and expected depths to objective sands (Use additional sheets as needed):

Objective - shallow Eocene sand + 500 feet.

I understand that this plan of work must receive approval in writing by the Director of the State Department of Geology and Mineral Industries.

Approved May 25, 19 60except as follows: **Surface casing to be run to firm impermeable formation and cemented on the outside from top to bottom.**

DEPARTMENT OF GEOLOGY & MINERAL INDUSTRIES

By [Signature] Director[Signature]
COMPANY OR OPERATORBy [Signature]Position Manager

Send communications regarding well to:

Name [Signature]Address Box 926 Canby Ore