Form 6-54

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator **Ross R. Mitchell & Associates** Field **Dallas area**

Well No. **Bliven No. 3** , Sec. **10** , T. **8 S** R. **5 W** W.B. & M.

Signed **Ross R. Mitchell**

Date **August 4, 1960** Title **Manager**
(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date	
6-28-60 to 6-30-60	Moved in and rigged up small rotary equipment.
7- 1-60	Spudded July 1, 1960. Drilled 7-7/8" hole to 50 feet. 6-5/8" O.D. casing cemented at 50 feet with 6 sacks of construction cement.
7- 2-60 to 7- 7-60	Installed 6" gate valves on surface casing and flow pipe. Drilled out 8 feet of cement in the bottom of the 6-5/8" casing. Drilled 6" hole to 500 feet.
7-8-60	Shut down to go after a core barrel.
7-9-60	Drilled 6" hole to 580 feet.
7-10-60	Shut down.
7-11-60 to 7-12-60	Removed rotary equipment. <u>Bailer test</u> Bailed the hole dry. There was a small flow of inflammable gas. About one barrel of salt water flowed into the hole in two hours. A trace of oil was reported.
7-13-60	Checked fluid level at 330 feet - salt water had risen 250 feet during the night.

Form 6-54

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator **Ross R. Mitchell & Associates** Field

Well No. **Bliven No. 3** , Sec. , T. R. W.B. & M.

Signed

Date Title

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date

7-13-60 **(Cont.)**

Filled the hole with drilling mud.

Cement plug (60-40'). Dumped 5 sacks of construction cement in 6" hole at 60 feet with a bailer.

Top plug (10-0'). Filled the casing with mud to 12 feet. Put a 10-foot cement plug in the top of the 6-5/8" casing. Cut off the casing 2 feet below ground level and welded on a steel plate.

Abandoned 7-13-60.

Note:-History was written from daily tour sheets by V. C. Newton, Petroleum Engineer, State of Oregon Department of Geology and Mineral Industries.