

RECEIVED-PT 17

FEB 2 1982

DEPT OF GEOLOGY

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Diamond Shamrock Field Wildcat  
Well No. Boise Cascade 11-14 Sec. 14, T 7N, R 7W, \_\_\_\_\_ W. B. & M.  
Location 722' S 1370' E from NW corner Elevation above sea level 570 feet  
All depth measurements taken from top of KB, which is 13.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 1-28-82 Signed [Signature]  
John C. Schmidt District Eng Title \_\_\_\_\_  
Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling 3/10/81 Completed drilling 5/4/81 Drilling tools Cable Rotary  
Total depth 7864 Plugged depth \_\_\_\_\_  
Junk \_\_\_\_\_  
GEOLOGICAL MARKERS DEPTH  
Scappoose Fm (equiv.) 120  
Pittsburg Bluff (equiv.) 480  
Keasey (equiv.) 4024  
Cowlitz (equiv.) 5905

Commenced producing N/A Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production	N/A					
Production after 30 days	N/A					

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
9 5/8"	766'	Surface	36.0#	New	Smlss	K-55	13 1/2"	535	N/A
5 1/2"	7864'	Surface	17&15.5#	New	Smlss	K-55/N-80	8 3/4"	865/350	4232' DV too
Production string of 5 1/2" casing cut off & removed at 2600'.									

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
N/A	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				