


STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building, Portland 1, Oregon



WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Reserve Oil and Gas Company Field McCoy Area  
Well No. Roy-L & G Bruer No. 1 Sec. 31, T. 6 S, R. 4 W W. B. & M.  
Location 2334' S, 1855' W of the NE Cor. Elevation above sea level 346.3 feet  
All depth measurements taken from top of Kelly bushing, which is 12 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 6-13-60 Signed R. Mangold  
W. H. LeRoy T. Gray  
Engineer or Geologist Drilg Superintendent  
(President, Secretary or Agent)

Commenced drilling 5-8-60 Completed drilling 6-1-60 Drilling tools Rotary  
Total depth 5549' Plugged depth 550 - 462 GEOLOGICAL MARKERS DEPTH  
Junk None Spencer Fm 0 - 3500'  
Yamhill Fm (?) 3500 - 5549'

Commenced producing Never produced Date \_\_\_\_\_ Flowing/gas lift/pumping  
(cross out unnecessary words)

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production					
Production after 30 days					

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
<u>10-3/4"</u>	<u>529</u>	<u>3</u>	<u>32.75</u>	<u>New</u>	<u>Smlss</u>	<u>H-40</u>	<u>15-1/2"</u>	<u>350</u>	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				

*Mil*