

WELL SUMMARY REPORT
 (Submit in duplicate)

RECEIVED
 SEP 24 1984

Operator Reichhold Energy Corporation Field Mist
 Well No. Busch 14-15 Sec. 15, T 6N, R 5W
 Location 317'N & 1187'E of SW $\frac{1}{4}$ Elevation above sea level 529.32 feet
 All depth measurements taken from top of Kelly Bushing, which is 12.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date September 19, 1984

Signed Yodd Thomas

Engineer or Geologist _____ Superintendent _____
 Title Field Operations Supervisor
 (President, Secretary or Agent)

Commenced drilling 8/2/84 Completed drilling 8/7/84 Drilling tools Cable Rotary

| Total depth | Plugged depth | GEOLOGICAL MARKERS | DEPTH |
|-------------|---------------|--------------------|-------|
| <u>2259</u> | | | |
| Junk | | | |
| | | | |
| | | | |

Commenced producing waiting on hook up Date _____ Flowing/gas lift/pumping
 (cross out unnecessary words)

| | Clean oil bbl per day | Gravity Clean oil | Percent water including emulsion | Gas Mcf. per day | Tubing Pressure | Casing Pressure |
|--------------------------|-----------------------|-------------------|----------------------------------|-------------------|-----------------|-----------------|
| Initial production | | | | <u>3.04 MMCFD</u> | <u>800 PSI</u> | |
| Production after 30 days | | | | | | |

CASING RECORD (Present Hole)

| Size of casing (A.P.L) | Depth of shoe | Top of casing | Weight of casing | New or second hand | Seamless or Lapweld | Grade of casing | Size of hole drilled | No. of sacks of cement | Depth of cementing if through perforations |
|------------------------|---------------|----------------|------------------|--------------------|---------------------|-----------------|----------------------|------------------------|--|
| <u>8 5/8"</u> | <u>406</u> | <u>Surface</u> | <u>24#</u> | <u>New</u> | <u>Seamless</u> | <u>K-55</u> | <u>12 1/2"</u> | <u>200</u> | |
| <u>5 1/2"</u> | <u>1754</u> | <u>Surface</u> | <u>15.5#</u> | <u>New</u> | <u>Seamless</u> | <u>K-55</u> | <u>7 7/8"</u> | <u>162</u> | <u>Shoe - 1,000'</u> |
| <u>2 3/8"</u> | <u>1462</u> | <u>Surface</u> | <u>4.7</u> | <u>New</u> | <u>Seamless</u> | | <u>Inside 5 1/2"</u> | | |

PERFORATIONS

| Size of casing | From | To | Size of perforations | Number of rows | Distance between centers | Method of perforations |
|----------------|-----------------|-----------------|----------------------|----------------|--------------------------|------------------------|
| <u>5 1/2"</u> | <u>1524 ft.</u> | <u>1556 ft.</u> | <u>1" hole</u> | <u>1</u> | <u>4 shots/ft</u> | <u>SSBII</u> |
| <u>5 1/2"</u> | <u>1564 ft.</u> | <u>1579 ft.</u> | <u>1" hole</u> | <u>1</u> | <u>4 shots/ft</u> | <u>SSBII</u> |
| | ft. | ft. | | | | |
| | ft. | ft. | | | | |
| | ft. | ft. | | | | |

Electrical Log Depths 2256' (Attach Copy of Log)