

WELL SUMMARY REPORT  
 (Submit in duplicate)

Operator Reichhold Energy Corporation Field Mist  
 Well No. C.C. #4 RD. #1 Sec. 15, T. 6N, R. 5W, W. B. & M.  
 Location Mist, 867' S, 1149' W from N.E. cor Sec 15 Elevation above sea level 765.03 feet  
 All depth measurements taken from top of Kelly Bushing, which is 11.40 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 7-27-82 Signed Tim Williamson  
 Title Drilling Superintendent  
 Engineer or Geologist \_\_\_\_\_ Superintendent \_\_\_\_\_  
 (President, Secretary or Agent)

Commenced drilling 7-10-82 Completed drilling 7-24-82 Drilling tools Cable Rotary  
 Total depth 2894 Plugged depth ---- GEOLOGICAL MARKERS DEPTH  
 Junk \_\_\_\_\_

Commenced producing 7/24/82 Date \_\_\_\_\_  
 Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production				<u>2250</u>	970	980
Production after 30 days						

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
7"	401	0	20#	New	Seamless	K-55	9 5/8	200	
4 1/2"	2679.05	0	10.5	New	Seamless	K-55	6 1/4	75	
2 3/8"	2276.17	0		New	Seamless				

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
4 1/2"	2403 ft.	2409 ft.	24 1/8 holes		4 shots per ft.	1 9/16 SSB
	2367 ft.	2490 ft.	88 1/2 holes		" "	"
	2347 ft.	2367 ft.	80 1/2 holes		" "	"
	2321 ft.	2337 ft.	64 1/2 holes		" "	"