

STATE OF OREGON
 DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
 1069 State Office Building Portland 1, Oregon

HISTORY OF OIL OR GAS WELL
 (Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator REICHHOLD ENERGY CORPORATION

Field MIST

Well No. Columbia County 12-9 RD.#1, Sec. 9, T. 6N R. 5W W.B. & M.

Signed *Tim Williamson*

Date March 10, 1982

Title Drilling Superintendent
 (President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

- | | |
|---------|---|
| Date | |
| 2-23-82 | Rigged up Bop's, tested same. Drilled out cement plug, POH to pickup Dyna Drill and directional tools drill, Depth 555' <i>(BOP about 450')</i> |
| 2-24-82 | Drilled to 973' |
| 2-25-82 | Drilled to 1233' |
| 2-26-82 | Drilled to 1616' |
| 2-27-82 | Drilled to 1881' |
| 2-28-82 | Drilled to 2376' |
| 3- 1-82 | Drilled to 2875' <i>AD</i> |
| 3- 2-82 | Drilled to <u>2917'</u> , POH to log, logging with Welex
Ran Dual Induction, Velocity, & Dip logs |
| 3- 3-82 | Circulation and waiting on orders |
| 3- 4-82 | Plugged well @ 2917'-2205' and 505'-217' |
| 3- 5-82 | Tagged plug @ 217' with Dennis Olmstead and released rig @ 12 noon 3-5-82 |