

WELL SUMMARY REPORT  
 (Submit in duplicate)

Operator REICHOLD ENERGY CORPORATION Field Mist  
 Well No. C.C. 13-1 R.D.#1 Sec. 1, T. 6N, R. 5W, Mist W. B. & M.  
 Location \_\_\_\_\_ Elevation above sea level 1163.2 feet

All depth measurements taken from top of Kelly Bushing, which is 11.40 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 6-23-82 Signed Tom Williamson  
 \_\_\_\_\_ Title Drilling Superintendent  
 Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling 4-23-82 Completed drilling 5-14-82 Drilling tools Cable Rotary  
 Total depth 3027 Plugged depth \_\_\_\_\_ GEOLOGICAL MARKERS DEPTH  
 Junk \_\_\_\_\_

Commenced producing June 3, 1982 Date \_\_\_\_\_ Flowing/gas lift/pumping  
 (cross out unnecessary words)

Initial production  
 Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
NA	NA	0	1920	750	798

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
7"	436	0	20	NEW	SEAMLESS	K-55	8 5/8	300	
4 1/2"	2822	0	10.5	NEW	SEAMLESS	K-55	6 1/4	100	
2 3/8"	2378	0		NEW	SEAMLESS	K-2	Inside 4 1/2"	--	----

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
4 1/2"	2822 ft.	0 ft.		1	4 per foot	Welex Sidewinder
	2378 ft.	2387 ft.				
	2377 ft.	2402 ft.				
	2407 ft.	2412 ft.				
	ft.	ft.				

Electrical Log Depths \_\_\_\_\_ (Attach Copy of Log)