

MISCELLANEOUS NOTICES AND REPORTS ON WELLS AND STRATIGRAPHIC HOLES (Submit in triplicate)

This is a combined form, use only portions pertinent to your needs.

RECEIVED-PTI n NOV 12 1980

To comply with rules and regulations adopted pursuant to ORS 520 (Chapter 667 OL 1953).

Table with 2 columns: Notices and Reports. Notices include 'Notice of intention to plug well & suspend' (checked XXX), 'Notice of intention to make production test', 'Notice of intention to abandon well', 'Notice of intention to test casing shut-off', 'Notice of intention to redrill or deepen well', 'Notice of intention to shoot or chemically treat well', and 'Notice of intention to complete well'. Reports include 'Report on plugging well (use form 5)', 'Report on making formation test', 'Report on making production test', 'Report on abandoning well', 'Report on testing casing shut-off', 'Report on redrilling or deepening well', 'Report on shooting or chemically treating well', and 'Report on completion of well'.

Submit notices in triplicate before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Department or agent, of the plan submitted.

Submit reports in triplicate within 20 days after the work specified is completed.

BAKERSFIELD, CA, ~~XXXX~~ NOVEMBER 6 1980

Department of Geology and Mineral Industries Portland, Oregon

Following is a ~~XXXXXXXXXXXXXXXXXXXXXXXXXXXX~~ notice of intention to do certain work as described below at the REICHHOLD ENERGY CORPORATION Company or Operator

COLUMBIA COUNTY

Well No. 14-2 in

of sec. 2, T. 6N, R. 5W, W.B. & M., MIST field, County. The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on form on and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.) 19

The present condition of the well, including complete casing record, is as follows (Use additional sheets as needed):

- 1. 7" surface casing cemented at 522'.
2. 6-1/4" hole drilled to 3582'.
3. No gas sands were found



ATTACHED IS A COMPLETE DETAILED ACCOUNT OF ~~XXXXXXXXXXXXXXXXXXXXXXXXXXXX~~ PROPOSED WORK. THE ATTACHMENT

IS PART OF THIS NOTICE OR REPORT AND IS CONSIDERED COVERED BY THE AFFIDAVIT.

- 1. Hang drill pipe at 3088' and pump in 50 sacks of cement. Calculated to fill to 2818'.
2. Hand drill pipe at 589' and pump in 75 sacks of cement. Top of plug to be located at or above 472'.

Last produced Cap 7" casing at surface and suspend well (date) (net oil) (gravity) (cut)

Approved 19 except as follows DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES Director

REICHHOLD ENERGY CORPORATION Company or operator By W.S. McBurnie Position W. S. MC BURNIE, ENGINEER Send communications regarding well to Name W. F. COVERT Address P. O. BOX 810 ST. HELENS, OR 97051