WELL Columbus County Test

COMPANY Reynolds Energy Co.

AREA West Reynolds Basin

LOCATION 200'N & 200'E OF SW CORNER SEC. 2, TWP 10S, RGE 13E

COUNTY, STATE Columbus, Oregon

- WEGE -
WESTERN GEO-ENGINEERS
"A SERVICE TO THE OIL AND GAS INDUSTRY"

LITHOLOGY SYMBOLS

REMARKS

Well Elev. GL 1154±0'
KB 1170±0'
Salinity of mud sys.
Filtrate @ 150°F 10 cc.
Gas trap at 1200' 90 units
Mud circulating time 4 hrs
(Surface)

Pipe Summary

CASING

13"	76'	Cmt'd
9 5/8"		
7"		
4½"		

MUD DATA

W WEIGHT	
V VISCOSITY	
WL WATER LOSS	
FC FILTER CAKE	
GL GAIN OR LOSS	

S SALINITY	
R RESISTIVITY	
T TEMPERATURE	
BIT DATA	
NB NOZZLE SIZE	
BHA BOTTOM HOLE ASSY.	

LEGEND

CR - CORE BIT
WL - WIRE LINE CR
OTHER DATA
DST - DRILL STEM TEST
CC - CONNECTION GAS
CARBIDE GAL.

CR - CIRCULATE RETURNS
DS - SIDE WALL CORES
DST - DRILL STEM TEST
GEO INTERVAL
CORE INTERVAL

DATE Jan/Feb/80 TO 12-/--/80 DEPTH 18' TO 3600' ENGINEERS Thomas Gutsch

PUMPED PIT

OIL IN MUD or CUTTINGS Tr = Fair ++ Good +++ VGS max

MUD ANALYSIS

Total Units Gas _____

MFC MAX _____ BLANKET _____ MIN

10 20 30 40 50 0 50 100 150 200 250 300 350 400 450 500

CUTTING ANALYSIS

Total Gas _____

MFC MAX _____

Mud Data
Formation Tests
Cores/Sidewalls
Surveys
E Log

REMARKS

WESTERN GEO-ENGINEERS

Drilling Rate in ft/hr

Bit Data

SAMPLE LITHOLOGY

DEPTH

Griffing Rig #3

Drilled 12¼" hole to 76'. Ran 13" 54.5# csg. Cmt'd w/ 75 sx Class A cmt. Circ. cmt to surface.

Drilled out cmt & shoe. Drilled 12¼" hole to 1000'. Ran 9 5/8" 36# csg. Cmt'd w/ 650 sx Class A cmt. Circ. cmt to surface.

Drilled out cmt & shoe. Drilled 8½" hole to 3600'. Ran 7" 23# csg. Cmt'd w/ 250 sx Class A cmt. Circ. cmt to surface.

Ran 4½" 11.6# csg. Cmt'd w/ 150 sx Class A cmt. Circ. cmt to surface.

Griffing Rig #3