

MISCELLANEOUS APPLICATION
 (In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest "C.C." 22B-19-65
 (Company or Operator) (Lease) (Well No.)
 Sec. 19 T 6N R 5W Surveyed Coordinates:
 SHL= 1,823' South and 1,214' East from the Northwest corner of Section 19
 BHL=
 Wildcat: NA (or) Field Name: Mist Gas County: Columbia
 Date: September 4, 1997 Signature: Rob Lucas

Use this form for telephone applications to deepen, rework, abandon, or any other proposed procedure on an existing well.

This form becomes a permit when signed and dated by DOGAMI in the box below.

The present condition of the well, including complete casing record, is as follows:


Casing(s): 8-5/8" 24# J-55 cemented at 506'
 4-1/2" 10.5# J-55 cemented at 2,939'
 Perforations: 6 SPF from 2,878'-2,890'
 Tubing Detail: 90 joints of 2-3/8" 4.7# J-55 EUE tubing set at 2,829'

Plug below ↓

Following is a detailed account of proposed work:

1. Circulate well with lease water, and establish injection rate into perforations. Nipple down production tree, install 7-1/16" 3M BOPE and test.
2. Pull out of hole laying down tubing. Remove BOPE and install production tree. Release well-service rig.
3. Fill 4-1/2" casing with cement from 2,890'-surface.
4. Cut off wellhead and cut casings 5' below ground level. Set 25' cement plug from surface in 4-1/2" X 8-5/8" annulus if necessary.
5. Restore location to original condition.

DOGAMI approved September 8, 1997
 DOGAMI to witness BOPE test and pumping of cement.
 by *Dennis Zolusko*



Spacing Unit
 9/19/97 9:05 am
 Cement w/ 257 cu ft
 Class G Cement.
 (108 sx)
 Plugged 9:40 am.

* Establish injection rate with water before pumping cement. If cannot establish rate, cement through tubing.

Injection Rate 4 bbls/minute @ 160 psi.

From: Rob Lucas To: Dennis/Dan

Date: 8/9/96 Time: 7:57:42 PM

Page 3 of 4

VERBAL APPROVAL FORM

MISCELLANEOUS APPLICATION
 (In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest "Columbia County" 22B-19-65
 (Company or Operator) (Lease) (Well No.)
 Sec. 19 T 6N R 5W Surveyed Coordinates (if directional, BHL & SHL): 1,823' South and 1,214' East from the Northwest corner of Section 19
 Wildcat: (or) Field Name: Mist Gas Field County: Columbia
 Date: August 9, 1996 Signature: Rob Lucas

Use this form for telephone applications to deepen, rework, abandon, or any other proposed procedure on an existing well.

This form becomes a permit when signed and dated by DOGAMI in the box below.


The present condition of the well, including complete casing record, is as follows:

CASING(S): 8-5/8" 24# J-55 cemented at 506'
 4-1/2" 10.5# J-55 cemented at 2,939'
 PERFORATIONS: 6 SPF from 2,878'-2,935'
 TUBING DETAIL: 87 joints of 2-3/8" 4.7# J-55 EUE tubing set at ±2,739'

Following is a detailed account of proposed work:

1. Circulate well to static condition and install 7-1/16" 3M BOPE.
2. Set cement plug from 2,900'-2,937' (E.D.). Run tubing and land at ±2,859'.
3. Run in hole with 1-1/16" thru tubing gun and perforate 6 SPF : 60° off-center phased on 2 planes from 2,878'-2,890'.
4. Return well to sales line.

DOGAMI approved AUG 15, 19 96
 CALL DOGAMI TO WITNESS PRESSURE TEST OR FUNCTION TEST OF BOPE
 by *Dennis Zolusko*



Spacing Unit