

**STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES**

800 NE Oregon St #28 Portland, OR 97201

WELL SUMMARY REPORT
(In compliance with rules and regulations pursuant to ORS 520)

Enerfin Resources Northwest

"Columbia County"

32-28-75 (Hadorasaur)

(Company or Operator)

(Lease)


(Well No.)

Sec. 28 T 7N R 5W Surveyed Coordinates:

SHL- 1,818.70' South and 2,231.71' West from the Northeast corner of Section 28 (X=1 287 239.6935 Y=886 284.1802)

BHL= NA

Wildcat: NA (or) Field Name: Mist Gas County: Columbia

Signature: 

Date: August 19, 1999

Position: Consultant

Commenced drilling: July 26, 1999 Completed drilling: July 30, 1999 P&A: NA

Total depth: 2,863' Redrill depth: _____

Logs run: Mud log from 50'-2,863'; AIT-DSN-CDL-BHC-GR from 2,882'-476' (shoe); NDL-CBL-CCL from 2,807'-550'

Casing Record

Size of hole	Size of casing	Wt. in lbs. per ft.	Grade Type	Depth	Amount of cement
25"	12"			30'	Surf. Pour
9-7/8"	7"	23#	J-55/LT&C	569'	285 sx
6-1/4"	2-7/8"	6.5#	J-55/EUE	2,863'	275 sx

Geological Marker

Depth

Plugs	<u>Sager Creek</u>	<u>1,405'</u>
	<u>Keasey</u>	<u>1,450'</u>
	<u>Cowlitz</u>	<u>2,550'</u>
	<u>C&W</u>	<u>2,650'</u>
Junk	<u>None</u>	<u>2,800'</u>
	<u>Greys River Basalt</u>	

Perforations or Liner

Size of casing	From	To	Shots/ft.	Method of Perforating		
				Jet	Bullet	Slotted Liner
2-7/8"	2,666'	2,678'	4	✓		

Initial Production

Date	Clean Oil bbl/day	Gravity	Percent Water	F.T.P.	F.C.P.	S.I.T.P.	S.I.C.P.
08-17-99 (test)	143 MCFD				378		626