

APR 15 1985

DEPT. OF GEOLOGY
& MINERAL INDUS

PLUGGING RECORD

(In compliance with rules and regulations pursuant to ORS 520, this form must be submitted within 60 days after plugging.)

Reichhold Energy Corporation Columbia County 43-34
(Company or operator) (Lease) (Well No.)
Sec. 34, T. 6N R. 5W W.B.&M. Surveyed Coordinates: 2116' North and
1079' West of SE corner
Wildcat: Yes (or) Field Name: County:

Date well was plugged: March 27, 19 85

The interval between plugs shall be filled with a heavy mud-laden fluid. Was the well filled with mud-laden fluid as required? Yes How was the mud applied? Pumped

Please furnish the following information:

CASING: (1) Size (2) Weight (3) Depths set PLUGS: (1) Type (2) Depth/interval (3) Amount of cement

Casing: 8 5/8" 24# set @ 431'

Plugs: Original hole

Class "G" cement plug set @ 1427' - 1277' with 45 sacks

Class "G" cement plug set @ 560' - 325' with 108 sacks

Plug polished off to 570' & well redrilled

Redrill #1

Class "G" cement plug set @ 1553' - 1440' with 50 sacks

Class "G" cement plug set @ 499' - 365' with 56 sacks

AFFIDAVIT

STATE OF Oregon }
County of Columbia } ss.

I, Todd Thomas, being first duly sworn, depose and say that I have knowledge of the facts stated herein, that they are true and correct, and that I am authorized to make this report.

Signature: Todd Thomas
Position: Field Operations Supervisor

Subscribed and sworn to before me this 10th day of April, 19 85

My commission expires February 13, 1988

Signature: Mary A. Hawkes (Mary A. Hawkes)
Notary Public for State of Oregon