

## WELL HISTORY

DEPT OF GEOLOGY  
& MINERAL INDUSTRIESOregon Natural Gas Development Corporation  
Well Crown-Zellerbach No. 1Section 13-2S-10W, W.B. & M.  
Tillamook County, Oregon

November, 1979

30, Brinkerhoff-Signal moved in Rig No. 61 and rigged up.

December, 1979

1, Rigging up.

2, Spudded in at 6:00 P.M. with 12-1/4" bit and drilled ahead.

169' Siltstone  
Survey at 140' 0° 30'

3, 498' Siltstone  
Survey at 350' 0° 45'  
Survey at 444' 1° 45'

4, 673' Siltstone  
Survey at 502' 1° 45'

Ran 18 joints (inc. landing joint) or 673.88' of 8-5/8" 24# K ST&C casing equipped with B&W guide shoe and an insert fill-up valve on top of shoe joint. Cemented around shoe at 667' with 350 sacks of Class II Cement treated with 2% CaCl<sub>2</sub>. Used top rubber plug and displaced with 3% over calculated displacement. Did not bump plug. Cement returns at surface.

## CASING DETAILS

Guide Shoe	1.06
1 Joint	38.33
Insert Fill-up Valve	-0-
16 Joints	615.14
1 Landing Joint	19.35
	673.88
Above KB	7.35
Shoe @	666.53

-1-

## WELL HISTORY

Oregon Natural Gas Development Corporation  
Well Crown-Zellerbach No. 1Section 13-2S-10W, W.B. & M.  
Tillamook County, Oregon

December, 1979

5, Backed out landing joint and install 8" Series 900 Shafer Screw-on Casing Head.

Installed and tested BOP equipment. Witnessed by Department of Geology and Mineral Industries.

6, Waited on Cement.

Drilled out plug, insert, cement below and shoe with 7-7/8" bit and drilled ahead.

774' Siltstone

7, 1,260' Siltstone  
Survey at 795' 2° 0'  
Survey at 1,054' 2° 0'

8, 1,942' Siltstone  
Survey at 1,314' 2° 0'  
Survey at 1,567' 1° 30'

9, 2,264' Siltstone  
Survey at 2,193' 4° 0'

10, 2,477' Siltstone  
Survey at 2,287' 3° 45'  
Survey at 2,319' 3° 30'  
Survey at 2,401' 3° 30'

11, 2,744' Siltstone and Sand  
Survey at 2,700' 3° 30'

12, 3,038' Siltstone and Sand  
Survey at 2,988' 3° 0'

-2-

## WELL HISTORY

Oregon Natural Gas Development Corporation  
Well Crown-Zellerbach No. 1Section 13-2S-10W, W.B. & M.  
Tillamook County, Oregon

December, 1979

13, 3,233' Siltstone and Sand

14, 3,457' Siltstone  
Survey at 3,324' 2° 0'

15, 3,680' Siltstone  
Survey at 3,571' 2° 0'

16, 3,904' Siltstone & Volcanics  
Survey at 3,869' 4° 0'

17, 4,097' Volcanics  
Survey at 4,052' 4° 0'

18, 4,290' Volcanics

19, 4,453' Volcanics

20, 4,588' Volcanics  
Survey at 4,588' 2° 45'

21, 4,675' Volcanics

22, 4,798' Volcanics

23, 4,918' Volcanics

24, 5,012' Volcanics

25, 5,101' Volcanics  
Survey at 5,071' 2° 0'

26, 5,170' Volcanics  
Survey at 5,163' 1° 45'

-3-

## WELL HISTORY

Oregon Natural Gas Development Corporation  
Well Crown-Zellerbach No. 1Section 13-2S-10W, W.B. & M.  
Tillamook County, Oregon

December, 1979

27, 5,263' Volcanics

28, 5,400' Volcanics

29, 5,531' Volcanics

30, 5,703' Volcanics

31, 5,794' Volcanics  
Survey at 5,794' NG

January, 1980

1, 5,888' Volcanics

2, 5,951' Volcanics  
Survey at 5,889' 4° 0'

3, 6,041' Volcanics

4, 6,127' Volcanics

5, 6,158' Volcanics

Attempted to run Wellex Induction-Electric Log. Stopped at 5,802'.

Ran in with bit and conditioned hole.

6, Ran Wellex Induction-Electric Log from 667' - 6,143'.

Ran Wellex Compensated Acoustic Velocity Log from 667' - 6,143'.

Wellex took Sidewall Samples. Descriptions attached.

7, Laid down excess drill pipe.

-4-

## WELL HISTORY

Oregon Natural Gas Development Corporation  
Well Crown-Zellerbach No. 1Section 13-2S-10W, W.B. & M.  
Tillamook County, Oregon

January, 1980

7, Plug No. 1: Hung drill pipe at 720' and pumped in and equalized 85 sacks of Class II Cement treated with 3% CaCl<sub>2</sub>. Cement in place at 3:20 P.M.

Located top of Plug No. 1 at 491' at 7:50 P.M.

Plug No. 2: Hung drill pipe at 62' and pumped in 20 sacks of Class II Cement treated with 3% CaCl<sub>2</sub>, which filled the surface casing with cement to the surface. Cement in place at 8:50 P.M.

8, Cut off surface casing 5' below ground level and welded on steel plate

Hole abandoned in this condition.

-5-