

NOV 14 1980

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator Reichhold Energy Corporation Field Mist  
 Well Crown Zellerbach 22-6 sec. 26, T. 6N, R. 4W, W. B. & M.  
 Section 1584'S. 468'W. fr N/4 Corn Elevation above sea level 1424.6 feet  
 All depth measurements taken from top of KB, which is 10.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 10/18/80 Signed William S. [Signature]  
W. Bruer D. Dawson Title Engineer  
~~Geologist~~ Superintendent (President, Secretary or Agent)

Commenced drilling	<u>9/24/80</u>	Completed drilling	<u>10/1/80</u>	Drilling tools	Cable Rotary
Total depth	<u>3671 OH</u>	Plugged depth	<u>See below</u>	GEOLOGICAL MARKERS	
<del>2265</del> R/D1	OH	R/D1	R/D2	DEPTH	
<u>2431 R/D2</u>	<u>2938-2722</u>	<u>2227-2011</u>	<u>2412-2196</u>		
	<u>528-453</u>	<u>528-445</u>	<u>528-145</u>		
			<u>14-34</u>		

Commenced producing ABN. Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

	Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production	NEVER PRODUCED					
Production after 30 days						

CASING RECORD (Present Hole)

Line of casing (A, B, C)	Depth of casing	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
<u>7</u>	<u>440</u>	<u>0</u>	<u>20</u>	<u>N</u>	<u>S</u>	<u>K</u>	<u>9 7/8</u>	<u>200</u>	

PERFORATIONS

Line	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
<u>NONE</u>	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				