

WELL SUMMARY REPORT  
(Submit in duplicate)

RECEIVED  
NOV 3 - 1980

Operator American Quasar Petroleum Field Wildcat  
Well No. Crown Zellerbach 30-33 Sec. 30, T 6N, R 4W, W. B. & M.  
Location NW 1/2 SE 1/4 Elevation above sea level 843 feet

All depth measurements taken from top of Kelly Bushing, which is 10.5 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 10/28/80 Signed John F. Works  
Engineer or Geologist Superintendent Title Division Drilling Engineer  
(President, Secretary or Agent)

Commenced drilling	<u>10/22/80</u>	Completed drilling	<u>10/25/80</u>	Drilling tools	<del>Cable</del> Rotary
Total depth	<u>2350</u>	Plugged depth	<u>Surf</u>	GEOLOGICAL MARKERS	
Junk	<u>None</u>				DEPTH
				<u>Cowlitz</u>	<u>720</u>
				<u>1st C&amp;W Sand</u>	<u>1050</u>
				<u>2nd C&amp;W Sand</u>	<u>1743</u>

Commenced producing	Date	Flowing/gas lift/pumping (cross out unnecessary words)
Initial production		
Production after 30 days		

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing ( A.P.L )	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
<u>12"</u>	<u>20'</u>	<u>Surf.</u>	<u>Conductor</u>					<u>4 yds</u>	<u>Ready Mix</u>
<u>7"</u>	<u>525'</u>	<u>Surf.</u>	<u>20#</u>	<u>New</u>	<u>Seamless</u>	<u>K55</u>	<u>9 7/8"</u>	<u>225</u>	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				