

PLUGGING RECORD

The owner or operator of any oil or gas well or stratigraphic hole shall file this form with the Director of the State of Oregon Department of Geology and Mineral Industries setting forth in detail the method used in plugging such well. The form must be filed within twenty (20) days after plugging for oil and gas wells, or within sixty (60) days for stratigraphic holes.

Rule L of rules and regulations adopted pursuant to ORS 520.095 (1) (13) (Chapter 667 OL 1953)

Operator Riddle Gas & Oil Producers, Oregon, Ltd. Field Riddle area  
 Pool \_\_\_\_\_  
 County Douglas

ADDRESS ALL CORRESPONDENCE CONCERNING THIS FORM TO:

Street Route 1, Box 54-A City Riddle State Oregon  
 Lease Name Harry Dayton Well No. 1 Sec. 34 T. 30 S R. 6 W  
 Date well was plugged July 18 1960.

Was the well filled with mud laden fluid, according to regulations of the Board of the State of Oregon Department of Geology and Mineral Industries? Hole bridged.

How was the mud applied? - - - Were plugs used? Cement If so, show all shoulders left for casing, depth of each, and size of casing, size and kind of plugs used, and depths placed. Also amount of cement and rock. Use additional sheets if necessary.

- 10-3/4", 32# surface casing cemented at 115 feet.
- 6-5/8" casing cemented at 950 feet with 250 sacks.
- 6" hole drilled to 1370 feet T.D.

Junk: Swab left in hole at 1046 feet - rope socket pulled out.  
 Was notice given, before plugging, to all available adjoining lease and land owners?

Riddle Gas & Oil LTD.  
 (Operator)

AFFIDAVIT

State of Oregon  
 County of Douglas

I, S. T. Humphrey, being duly sworn, say that I have knowledge of the facts stated herein, that they are true and correct, and that I am authorized to make this report.

Subscribed and sworn to before me this 12th day of August 1960

[Signature]

Notary public in and for Oregon

My commission expires MAY 10, 1964.

(See opposite side for plugging details)

Plugging details

1. Bridged 6-5/8" casing at 10 feet with a wood plug.
2. Put three sacks of construction cement in the top of the 6-5/8" casing.

Abandoned: 7-18-60