

STATE OF OREGON  
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES  
1069 State Office Building, Portland 1, Oregon

WELL SUMMARY REPORT  
(Submit in duplicate)

Operator El Paso Natural Gas Company Field Wildcat  
Well No. Spurrier Federal #1 Sec. 5, T 20S, R 44E, W. B. & M.  
Location 550' E/L, 330' N/L Elevation above sea level 2520' feet  
All depth measurements taken from top of Kelly Bushing, which is 2531' feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date January 21, 1955 Signed Leroy Bechte1  
Bechte1 Title Geologist  
Engineer or Geologist Superintendent (President, Secretary or Agent)

Commenced drilling November 25, 1954 Completed drilling January 12, 1955 Drilling tools Rotary  
Total depth 7470 drilled suggested depth P & A (275') GEOLOGICAL MARKERS DEPTH  
Junk None U Idaho Fm. 0-900'  
Grassy Mt basalt 900-1830'  
L. Idaho Fm basalt 1830'-~~4440~~  
Deer Butte Fm. 4440-6570'  
Rhyolite 6570-7470'  
Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping (cross out unnecessary words)

Initial production \_\_\_\_\_  
Production after 30 days \_\_\_\_\_

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
13 3/8"	295	0	48	New	Smless	H-40	17 1/4	265	Surface

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				