Form 3 1/54

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
1069 State Office Building Portland 1, Oregon

LOG AND CORE RECORD OF OIL OR GAS WELL

Permit No. 47

(Submit in duplicate)

In compliance with rules and regulations pursuant to ORS 520.095 (Chapter 667 OL 1953).

Operator HUMBLE OIL & REFINING COMPANY Field Silverton Hills Area

Well No. Francis E. Wicks et ux No.1, Sec. 11, T. 7-S, R. 1-E, _____ W. B. & M.

FORMATIONS PENETRATED BY WELL

Depth to Top of Formation	Depth to Bottom of Formation	Thickness	Drilled or Cored	Recovery	Description
0	390'	390'	D	-	Clay, sand and boulders
390'	563'	173'	D	-	Sand, shale and boulders
563'	857'	294'	D	-	Siltstone
857'	1165'	308'	D	-	Sand and shale
1165'	1517'	352	D	-	Clay
1517'	1975'	458'	D	-	Clay and sand
1975'	2129'	154'	D	-	Clay and volcanics
2129'	2224'	95'	D	-	Volcanics
2224'	2787'	563'	D	-	Sand and clay
2787'	2936'	149'	D	-	Sand and shale
2936'	6599'	3663'	D	-	Volcanics
6599'	6601'	2'	C	2'	Volcanics
6601'	7790'	1189'	D	-	Volcanics
7790'	7797'	7'	C	7'	Volcanics