Welex

COMPENSATED DENSITY LOG NEUTRON

COMPANY	AMERICAN QUASAR PETROLEUM CO.
WELL	HICKEY 9-12
FIELD	LEBANON API # 36-043-00013
COUNTY	LINN
STATE	OREGON
Location	1980' S & 990' E of THE N.W. CORNER
Other Services	AVL, DIGL, DIP
Sec.	9
Twp	12 S
Rge	2 W
Permanent Datum	G.L.
Elev.	329.6
Log Measured From	T.K.B.
Ft. Above Perm. Datum	10.5
Drilling Measured From	T.K.B.
Elev.: K.B.	340.5'
D.F.	
G.L.	329.0'

Date	1-28-81			
Run No.	TWO			
Depth—Driller	2162			
Depth—Welex	2161			
Btm. Log Inter.	2120			
Top Log Inter.	522			
Casing—Driller	9 5/8 @ 521	@	@	@
Casing—Welex	522			
Bit Size	8 3/4			
Type Fluid in Hole	LIGNO-SULF MUD			
Dens. | Visc.	90 | 70	|	|	|
pH | Fluid Loss	9.5 | 15.8 ml	| ml	| ml	| ml
Source of Sample	CIRCULATED			
R_m @ Meas. Temp.	3.46 @ 46 °F	@ °F	@ °F	@ °F
R_{mf} @ Meas. Temp.	4.58 @ 58 °F	@ °F	@ °F	@ °F
R_{mc} @ Meas. Temp.	3.22 @ 57 °F	@ °F	@ °F	@ °F
Source R_{mf} | R_{mc}	M | MEASURED	|	|	|
R_m @ BHT	1.44 @ 110 °F	@ °F	@ °F	@ °F
Time Since Circ.	4 HRS			
Max. Rec. Temp.	110 °F @ T.D.	°F @	°F @	°F @
Equip. | Location	8586 | WALLO	|	|	|
Recorded By	ANDERSON			
Witnessed By	MR. MANN			

Fold Here

EQUIPMENT DATA

GAMMA RAY				GAMMA DENSITY			
Run No.				Run No.			
Tool Model No.	102-A			Log Type	COMP.DENS.		
Diameter	3 5/8"			Tool Model No.	125		
Detector Model No.	102-A			Diameter	3 5/8"		
Type	SCINT.			Detector Model No.	127		
Length	N/A			Type	SCINT.		
Distance to Source	240"			Length	N/A		
				Source Model No.	DCS		
GENERAL				Serial No.	DCS-		
Hoist Truck No.	8586			Spacing	N/A		
Instrument Truck No.	8586			Type	Cs 137		
Tool Serial No.				Strength	500 mc		

LOGGING DATA

GENERAL				GAMMA RAY				GAMMA DENSITY			
Run No.	Depths From	Depths To	Speed Ft/Min	T.C. Sec.	Sens. Settings	Zero Div. L or R	API G.R. Units per Log Div.	T.C. Sec.	Sens. Settings	Zero Div. L or R	Units per Log Div.

Reference Literature:

RIG TIME: PAD 24299 LNS 27029 NEU 16161

Calibrator No.
Calibrator Value.
Date calibrated.

Service Ticket No. Remarks:

Welex does not guarantee the accuracy of any interpretation of log data, conversion of log data to physical rock parameters, or recommendations which may be given by Welex personnel or which may appear on the log or in any other form. Any user of such data, interpretations, conversions, or recommendations agrees that Welex is not responsible, except where due to gross negligence or wilful misconduct, for any loss, damages, or expenses resulting from the use thereof.

—100'

CALIPER Average Diameter In. 6" — 16"

GAMMA API Gamma Ray Units 0 — 100

COMPENSATED GAMMA DENSITY GMS/CC

$P_f = 1.0$

POROSITY AT Pg 2.65 G/CC

CORRECTION GMS/CC −.25 0 +.25

45% DENSITY POROSITY % −15%

45% NEUTRON POROSITY % (Sandstone) −15%

REPEAT SECTION