


APPLICATION FOR PERMIT TO DRILL NEW WELL OR STRATIGRAPHIC HOLE
(To be accompanied by a \$25.00 permit fee for new wells only and a surety bond conditioned as provided by law.)

San Francisco, California ~~xxxx~~ December 18 19 56

Department of Geology and Mineral Industries
Portland, Oregon

In compliance with rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) application is hereby made for permit to drill

a ~~(new well)~~ (stratigraphic hole) to be known as: Standard Oil Company of California Kirkpatrick
Well No. 1 in Sec. 6, T. 4 S., R. 21 E. W. B. & M.,
Condon Area ~~xxxx~~ Gilliam County.



T. 4 S., R. 21 E.
Section of land
Area 640 acres

* This well is see below ~~xxxx~~ xxxx ~~xxxx~~
~~xxxx~~ in ~~xxxx~~ Sec. 6, T. 4 S., R. 21 E., W.B.&M.

(Give location from section or other legal subdivision lines or corners. Cross out wrong directions)

Elevation of ground above sea level is 2,747 feet. All depth measurements are taken from top of Derrick Floor, which is 8 + feet above ground.

The lessee is Standard Oil Company of California, Western Division

Address 225 Bush Street, San Francisco, California

The lessor is Herbert L. Kirkpatrick and Janet Parman Kirkpatrick, husband and wife

LOCATE WELL CORRECTLY Address Condon, Oregon

We estimate that the first productive oil or gas sand should occur at a depth of about unknown feet.
We propose to use the following strings of casing and to land or cement them as herein indicated:

Size of hole	Size of casing	Weight in pounds per foot	Grade and type	New or second hand	Depth	Landed or cemented No. sacks cement
17"	13-3/8	51#	"J" seamless	New	1,000 +	Cemented (to surface)
Stratigraphic Test - Drill 8"-9" hole to total depth - now estimated between 8,000'-9,000'						
Casing requirements to be determined as drilling proceeds.						
Supplementary program will be filed prior to cementing any casing below 13-3/8.						

We propose to drill with ~~rotary~~ rotary tools.

If changes in the above plan become advisable we will notify you before cementing or landing casing.

Additional information including names of and expected depths to objective sands (Use additional sheets as needed):

*Coordinates: From northeast corner Section 6, 4,319 feet west along the north section line; thence southerly at right angle 2,909 feet. In SE $\frac{1}{4}$ of NW $\frac{1}{4}$ Section 6, Township 4 South, Range 21 East, W.B.&M. (See plat attached).

I understand that this plan of work must receive approval in writing by the Director of the State Department of Geology and Mineral Industries.

Approved December 21, 19 56
except as follows:
No exceptions.
DEPARTMENT OF GEOLOGY & MINERAL INDUSTRIES
By [Signature] Director

STANDARD OIL COMPANY OF CALIFORNIA
COMPANY OR OPERATOR
By [Signature] Contract Agent
By [Signature] Assistant Secretary
Send communications regarding well to:
Name Standard Oil Company of California
Address 557 Roy Street, Seattle, Washington