STATE OF OREGON DE. ..RIMENI OF GEOLOGY AND MINERAL INDUSTRIES

910 State Office Building

Portland, OR 97201

WELL SUMMARY REPORT (In compliance with rules and regulations pursuant to ORS 520)

Nahama	a_& Wea	gant En	ergy	Company	Long	gview	Fibre		12B-35-65		
(Company or Sec. 35 from N	. T _6N		W: ectio	Surveyed ((Le Coordinates (ease) if dire	ctional, BH	L & SHL)	(Well SHL: 1780	No.) 'S & 290'E	
					st		Cour	nty: Co	lumbia		
ate:						Signa	iture:	rent	Z. Pasca esident Oper	<i>Liaf</i> ations	
ommended dotal depth	rilling: : DIL-	6/2/9 3727' Sonic-G	3 R .37	Red 7201-501	Completed rill depth: _ ', FMS, 372	drilli 20'-10	00', CBL	93 1652'-6	P&A:	:	
	Size	4			Wt. in 11 per ft.	bs.	Grade Type		Depth	Amount of cement	
ASING ECORD	12 1/4"		8 5/8"		24#		J-55		500'	225 sx.	
	7 7/8"		4 1/2"		10.5 #		J-55		1717'	160 sx.	
nugs		,			Ge	eologic	al Marker			Depth	
Size of									Method of Perforating		
erforat:	ions	casin	lng 1/2"	From 1548	To 1552	Shots/ft. 4-SPF		Jet	Bullet	Slotted Line	
lner							V 1. 1.		X		
	_		M	CF/Day		<u> </u>					
		Date	KXIX	XamxxXiXI X/day	Gravity	Perc	ent F.T	. P. F	.C.P. S.I.	T.P. S.I.C.P.	

531

535

Summ4.For/7

roduction

nitial

9/2/93

1040