

WELL SUMMARY REPORT  
 (In compliance with rules and regulations pursuant to ORS 520)

Nahama & Weagant Energy Company Longview Fibre #43-32-65  
 (Company or Operator) (Lease) (Well No.)  
 Sec. 32, T 6N, R 5W Surveyed Coordinates (if directional, BBL & SHL): SHL: 2367'N & 1009'W  
 from SE corner of Sec. 32  
 Wildcat: \_\_\_\_\_ (or) Field Name: Mist County: Columbia  
 Date: December 30, 1993 Signature: *Trent R. Rosenfield*  
 Position: Vice President Operations

Commenced drilling: 8/24/93 Completed drilling: 8/31/93 P&A: \_\_\_\_\_  
 Total depth: 1909' Redrill depth: \_\_\_\_\_  
 Logs run: DIL/GR 1901'-502', Neutron & Density 1905'-900', FMS 1905'-900', Neutron/CBL/CCL 1828'-490'

CASING RECORD

Size of hole	Size of casing	Wt. in lbs. per ft.	Grade Type	Depth	Amount of cement
14 3/4"	10 3/4"	32.75#	H-40, ST&C	502'	288 sx
9 7/8"	7"	20#	K-55, ST&C	1839'	200 sx
	4 1/2" (Liner)	10#	Mesh wire Wrp.	Top 1793' Bottom 1909'	Gravel Packed

Plugs	Geological Marker	Depth
_____	_____	_____
_____	_____	_____
_____	_____	_____
Junk		
_____		
_____		

Perforations or Liner

Size of casing	From	To	Shots/ft.	Method of Perforating		
				Jet	Bullet	Slotted Line
4 1/2"	1793'	1909'				X

Initial Production

Date	MCF/Day		Gravity	Percent Water	F.T.P.	F.C.P.	S.I.T.P.	S.I.C.P.
	<del>9/19/93</del>	<del>10/19/93</del>						
10/19/93	1135				509	511		