

HISTORY OF OIL OR GAS WELL

(Submit in duplicate)

In compliance with rules and regulations adopted pursuant to ORS 520.095 (Chapter 667 OL 1953)

Operator REICHHOLD ENERGY CORPORATION

Field Mist

Well No. Libel 12-14

, Sec. 14

, T. 6N

R. 5W

W. B. & M.

Date 10-27-82

Signed *Tom Williamson*

Title Drilling Superintendent

(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date	Description
10-15-82	Spudded well and drilling 9 7/8" surface hole to 449'
10-16-82	Rig up casing crew and running 10 JTs 7" 2016' casing to a measured depth of 417.51'. Pumped 155 sxs class "G" cement to well.
10-17-82	Test B.O.P.'s with Bill King and drilling 6 1/4" hole @ 877'
10-18-82	Drilling 1506'
10-19-82	Drilling 2180'
10-20-82	T.D. well @ 2682' and logging with Schlumberger
10-21-82	Waiting on orders
10-22-82	Abandoned well, bottom plug set from 2300' to 1800' with 138 sxs class "G" cement. Top plug was set from 685' - 149' with 114 sxs class "G" cement.
10-23-82	Go in hole and tag plug @ 149' with Dennis Olmstead witnessing Released Rig 10-23-82