MEC COALEDO RANCH COREHOLE

GEOLOGIC WELL PROGNOSIS

COMPANY:

Methane Energy Corp.

WELL NAME:

Coaledo Ranch CH

ANTICIPATE SPUD DATE:

January 2005

TWIN:

NA

SURFACE LOCATION:

649' FNL, 210' FWL

ESTIMATED TD: 3950 Feet

LEGAL LOCATION:

SEC 15, T27S-R13W

ELEV. & TOPO: 70' ASL (Coquille)

COUNTY:

Coos

STATE:

Oregon

TERRAIN & ACCESS:

Hillside terrace; pasture/grazing land; access good near paved road;

OBJECTIVE FORMATION:

Upper & Lower Coaledo Fms.

HIGHEST DIP:

30° @ 2000',

TYPE OF WELL:

Vertical

FORMATIONS TO BE PENETRATED:	TOPS	EST. THICKNESS	DOM. LITHOS.	POSSIBLE CORE
Surface gravels	Surface	10'	Sand, gravel, clay	
Upper Coaledo Fm.	200°		Sandstone, siltstone	
#5 Bcd	420*	16'	coal	X
#4 Bed	500°	6'	∞al	X
#3 Bed	620'	10'	coal	X
#2 Bcd	7107	8'	coal	X
#1 Bed	8 40°	5'	coal	X
Middle Coaledo Fm.	1100'	1600'	Sandstone, siltstone	
Lower Coaledo Fm.	2700	To TD		
'F' Coal Zone	3100'	2'	coal	X
'E' Coal Zone	2825	8.	coal	X
'D' Coal Zone	3500°	8'	coal	X
'C' Coal Zone	3690	6°	coal	X
'B' Coal Zone	3840"	15'	coal	X
'A' Coal Zone	3930	15'	∞al	X
TD	(3950')		Sandstone, siltstone	

UNUSUAL CONDITIONS (LOST CIRC., SHALLOW BLOW-OUTS, WATER FLOWS, H2S, ETC.):

Unstable hole conditions; High bentonite clay content in sandstones; abandoned mines in neighboring sections.

MUD UNIT (DEPTHS & TYPE): One-man logging unit with gas detection, chromatograph, etc.

LOGGING PROGRAM: State required minimum

SPEC. SURVEYS:

Continuous core through coal intervals. Desorption sampling in coals. Sample produced

gas and water

REFERENCE WELLS: Northwest Exploration Fat Elk #1, Northwest Exploration Coos County #1

COMMENTS:

PREPARED BY:

S. Pappajohn, G. Hampton

GEOLOGIC WELL PROGNOSIS

COMPANY: Methane Energy Corp. | WELL NAME: Coaledo Ranch CH

ANTICIPATE SPUD DATE: January 2005 | TWIN: NA

SURFACE LOCATION: 649' FNL, 210' FWL | **ESTIMATED TD:** 3950 Feet

LEGAL LOCATION: SEC 15, T27S-R13W | ELEV. & TOPO: 70' ASL (Coquille)

COUNTY: Coos | STATE: Oregon

TERRAIN & ACCESS: Hillside terrace; pasture/grazing land; access good near paved road;

OBJECTIVE FORMATION: Upper & Lower Coaledo Fms. | <u>HIGHEST DIP</u>: 30° @ 2000'

TYPE OF WELL: Vertical

FORMATIONS TO BE PENETRATED:	<u>TOPS</u>	EST. THICKNESS	DOM, LITHOS.	POSSIBLE CORE
Surface gravels	Surface	10'	Sand, gravel, clay	
Upper Coaledo Fm.	200°		Sandstone, siltstone	
#5 Bed	420'	16'	coal	X
#4 Bed	500°	6'	coal	X
#3 Bed	620'	10'	coal	X
#2 Bed	710'	8,	çoal	X
#1 Bed	840'	5'	coal	X
Middle Coaledo Fm.	1100`	1600'	Sandstone, siltstone	
Lower Coaledo Fm.	2700'	To TD		
'F' Coal Zone	3100'	2'	coal	X
'E' Coal Zone	2825'	8'	coal	X
'D' Coal Zone	3500'	8'	coal	X
'C' Coal Zone	3690'	6'	coal	X
'B' Coal Zone	3840'	15'	coal	X
'A' Coal Zone	3930'	15'	coal	X
TD	(3950')		Sandstone, siltstone	

UNUSUAL CONDITIONS (LOST CIRC., SHALLOW BLOW-OUTS, WATER FLOWS, H2S, ETC.):

Unstable hole conditions; High bentonite clay content in sandstones; abandoned mines in neighboring sections.

MUD UNIT (DEPTHS & TYPE): One-man logging unit with gas detection, chromatograph, etc.

LOGGING PROGRAM: State required minimum

SPEC. SURVEYS: Continuous core through coal intervals. Desorption sampling in coals. Sample produced

gas and water

REFERENCE WELLS: Northwest Exploration Fat Elk #1, Northwest Exploration Coos County #1

COMMENTS:

PREPARED BY: S. Pappajohn, G. Hampton