EPOCH
WELL LOGGING, INC.

COMPANY	DY Oil
WELL	"Neverstill" 33-3C
FIELD	Mist
LOCATION	933.4' South and 1255.21'E from the NE corner of Sec. 3C, T6N, R5W WBM
COUNTY, STATE	Columbia, Oregon
API WELL INDEX NO.	
ELEVATION	507.7' G.L., 519.1'K.B.
DATES FROM	7-31-89 TO 8-7-89
DEPTHS FROM	381'K.B. TO 2225'K.B.
SPUD DATE	7-30-89
DRILLING CONTRACTOR	Taylor Drilling, Rig #5
MUD COMPANY	Beaver Drilling Fluids Inc.
LOGGING GEOLOGISTS	Craig Anderson Jim Lestes

ABBREVIATIONS

NB	BIT	MW	MUD WEIGHT
RRB	RERUN BIT	VIS	FUNNEL VISCOSITY
RTB	RE-TIP BIT	PV	PLASTIC VISCOSITY
CB	CORE BIT	YP	YIELD POINT
T.G.	TRIP GAS	FL	FLUID LOSS (cc/30 min)
S.G.	SURVEY GAS	CL	PPM CHLORIDE ION
W.G.	WIPER GAS	RM	MUD RESISTIVITY
C.G.	CONNECTION GAS	RMF	FILTRATE RESISTIVITY
WOB	WEIGHT ON BIT	LAT	LOGGED AFTER TRIP
RPM	ROTARY REV/MIN	NR	NO RETURNS
PP	PUMP PRESSURE	PR	POOR RETURNS
SPM	STROKES/MIN	MUD TYPE	Lignosulfonate

CASING RECORD

8 5/8"	AT	381'K.B.
5 1/2"	AT	2206'K.B.
	AT	
	AT	

HOLE SIZE

12¼"	AT	385'
8 7/8"	AT	2225'K.B.
	AT	
	AT	

SAND/SANDSTONE	CLAY	LIMESTONE	TUFF
SHALE	DIATOMITE	DOLOMITE	FOSSIL
SILTSTONE	CONGLOMERATE	BASALT	MICA
LIGNITE	GLAUCONITE	PYRITE	

OIL: BASED ON LIVE OIL IN UNWASHED CUTTINGS AND PERCENT STAINING AND FLUORESCENCE OF WASHED SAMPLES.

PENETRATION

EPOCH WELL LOGGING, INC.

DRILL RATE (FT/HR)

drilling data

DEPTH

LITHOLOGY

ANALYSIS OF RETURNS

OIL — GAS — UNITS

TRACE | FAIR | GOOD | SHOW

DITCH — TOTAL GAS

CUTTINGS GAS

CALIBRATION 100 units = 2% methane by volume

CHROMATOGRAPH — PPM

METHANE, C-1, _____

ETHANE, C-2, _____

PROPANE, C-3, _____

BUTANES, C-4, _____4

PENTANES, C-5, _____5

Accessory Mineral Column

Example: Occ---g Com---c Abund.-c

Drill out of 8 5/8" csg @ 7:15pm, 7-31-89

8 5/8" casing @ 381'

NB #2, 7 7/8" Sec 5335, 20°, 45° azimuth, out

WOB 15,000 RPM 112 PP 450 SPM #1-#2

Ditch and Cuttings Gas 1x

TG 1u

NB #3, 7 7/8" Sec 5335

WOB 15,000 RPM 110 PP 800 SPM #2-#3

Ditch and Cuttings Gas 1x

No Discernible CO²s

WOB 15,000 RPM 110-120 PP 800 SPM #1-#60

SG + STG 3u

WOB 20-25,000 RPM 112 PP 950 SPM #1-#60

CG 4u

CG 4u

CG 3u

CG 3u

CG 1u

CG 2u

CG 2u

CG 4u

CG 4u

CG 5u

CG 3u

Swab 54 u gas on trip

CG 2u

WOB 15,000 RPM 110 PP 900 SPM #1-#60

WG 11u

CG 9u

CG 4u

SG 13u

Ditch Gas 10X

560u Ditch

Trip: WOB 25-35,000

Ditch Gas 1X

31u

WOB 25,000 RPM 110 PP 900 SPM #1-#3

CG 4u

CG 9u

CG 8u

CG 14u

CG 9u

CG 9u

CG 2u

WOB 18-30,000 RPM 110 PP 900 SPM #1-#4

WG 27u

TOTAL DEPTH = 2225'K.B.

DRILLERS DEPTH = 2225'

10¼" & 11½ mud: 5-18

Note: Pad clean out run prior to logging. Pulled out of hole to log. Pad clean out run prior to running 5½" casing.

Ref 2.2@ 35°F

NACL 2500ppm

Rm 5.10@ 75°F

Rmc 2.04@ 75°F

REMARKS

LITHOLOGIC DESCRIPTION

MUD PROPERTIES

SURVEYS, OTHER TEST DATA

Notes: all colors are referenced to the GSA color chart. All carbides are 400gas unless otherwise noted. All connection and survey gases are reported as units above background; trip and carbide gases are reported as maximum gas units.

Siltstone: dk yellish brn; mdy, firm, occ sft, sbblky, sbplty, v slit dispt (locally strong), v slit micromicaceous; no vis fluor; no vis cut.

Sandstone: wht-lt gray, clrs, clr to frstd, vf-mgr, predom vfgr, mod sorted, sbang to sbrd, mod hd, fri, wk calc cmt, dirty in part, no vis por, no vis fluor or cut; rare dk gry-blk lithics.

Clay: moderate brn; firm-sft; earthy texture, sbblky, sbplty, occ fissile; locally grades to claystone; occ micaceous; no calc; no fluor or cut.

Siltstone: medium gray; firm; earthy texture, sbblky, occ sbplty; occ micaceous; occ pyritic; no calc; no fluor or cut.

Claystone: dk gray-blk; firm-sft; earthy texture, sbblky, occ sbplty; occ micaceous; occ pyritic; no calc; no fluor or cut.

Sandstone: wht-v lt gray to clr, v lt gray-lt gray, clr to frstd, vf-mgr, predom vfgr, mod sorted, sbang to sbrd, mod hd, fri, wk calc cmt, dirty in part, no vis por, no vis fluor or cut; rare dk gry-blk lithics.

Siltstone: dk gry-blk; firm-sft; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Claystone: dk gry-blk; firm-sft; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Siltstone: dk gry-blk; firm-sft; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Siltstone: med gry-dk gry, firm; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Siltstone: med gry-dk gry, firm; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Siltstone: med gry-dk gry, firm; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Note: Clrs becmg slightly lter olv w/over grnish hues.

Siltstone: med to dk gry-olv gray, firm; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Siltstone: med gry-olv gray, firm; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Note: Clrs becmg slightly lter olv w/over grnish hues.

Siltstone: med to dk gry-olv gray, firm; earthy texture, sbblky, sbplty, occ fissile; occ micaceous; occ pyritic; no calc; no fluor or cut.

Siltstone: med