-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
[illegible]

Date June 14, 1966

Type Sidewall Sampler CST-Conventional with extra long wires.

Cores Examined By J. J. Stosur

Section Offshore, Oreg. Rge.

Area XX STILT

Well OCS-P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	% Oil Stain	Hydrocarbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Color of Cut	Color of Cut Fluor.	[illegible]	[illegible]
			Note: Run #1 - Shot 30 conventional bullets with extra long wires - recovered 30 samples. No barrel damage observed.										
650'	1½	1	Silt/Clay, light olive gray, imbedded microcrystalline milky white specks (kaolinite?), firm (Glacial?) crumbly, very slightly calcareous. Sampled for magnetic susceptibility.	C	0	0	0	0	0	0	0	0	X
670'	1 3/4	1	Silt/Clay, as above, megafossil fragment, (Glacial?) noncalcareous. Medium dark gray.	C	0	0	0	0	0	0	0	0	X
730'	1½	1	Sand, (deeper end of sample) moderately gray, predominantly very fine to fine, silty, well sorted loosely consolidated, water saturated, very calcareous, common biotite, abundant megafossil fragments. Wellbore end is muddy - has bit frags.	3	0	0	0	0	0	0	0	0	X
840'	1½	1	Silt, light gray, sandy, loosely consolidated, limey, strongly calcareous, common microbiotite. Common small carbonaceous fragments.	C	0	0	0	0	0	0	0	0	X
930	1½	1	Clay, silt, olive black, soft, slightly calcareous, common carbonaceous fragments, micaceous.	C	0	0	0	0	0	0	0	0	X
1000'	1 3/4	1	Clay, silt as above at 930'.	C	0	0	0	0	0	0	0	0	X
1030'	"	1	Clay, medium dark gray, soft, very calcareous.	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % Sand: C, 0-5%; 1, 5-30%; 2, 30-65%; 3, 65-85%; S, 85-100%.

**See Legend for oil shows (over)

NOTED
JUL 19 1966
FACKLER

-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
[illegible]

Date June 14, 1966

Type Sidewall Sampler CST-Conventional with extra long wires

Cores Examined By J. J. Stosur

Section Offshore, Oreg. Rge.

Area STILT

Well OCS-P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	% Oil Stain	Hydrocarbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Cut Color of Cut	Cut Color of Cut Fluor.	[illegible]	[illegible]
1150'	1½	1	Silt, olive black, soft, common microbiotite, trace of micropiryte crystals. Sampled for magnetic susceptibility.	C	0	0	0	0	0	0	0	0	X
1170'		1	Silt/Clay, olive black, firm, very slightly calcareous.	C	0	0	0	0	0	0	0	0	X
1240'	1 3/4	1	Silt/Clay, as at 1170', very calcareous, fossil fragments, medium dark gray.	C	0	0	0	0	0	0	0	0	X
1310'	"	1	Silt/Clay, medium gray, soft, plastic, very calcareous.	C	0	0	0	0	0	0	0	0	X

1380'	"	1	Silt/Clay, dark gray, firm, calcareous.	C	0	0	0	0	0	0	0	0	X
1475'	"	1	Silt/Clay, medium dark gray, firm, microbiotite, very calcareous.	C	0	0	0	0	0	0	0	0	X
1545'	"	1	Silt/Clay, olive gray, firm-crumbly, common microbiotite, slightly calcareous.	C	0	0	0	0	0	0	0	0	X
1600'	"	1	Silt/Clay, as above, one worn burrow, filled with very fine sand, micro fauna, slightly calcareous	C	0	0	0	0	0	0	0	0	X
1650'	1½	1	Silt/Clay, as at 1310' sticky. Olive gray. Sampled for magnetic susceptibility	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; S,85-100%. **See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
(SIDEWALL CORE REPORT)

Page 3 of 4

Date June 14, 1966
Type Sidewall Sampler CST-Conventional with extra long wires
Cores Examined By J. J. Stosur

Location Offshore, XX, Oreg. Rec.
Area [illegible]
Well OCS-P 075-1ET

DEPTH	REC.	RUN	DESCRIPTION	LITH. SYM.*	OIL SHOWS**								
							Sample Oil Fluor.			Cut		Summary	
					% Oil Stain	% Hydrocarbon Odor	%	Inten.	Color	Color of Cut	Color of Cut Fluor.	[illegible]	[illegible]
1725'	1¾	1	Sand, dark gray, lower v. fine to fine, silty moderately sorted loosely consolidated, slightly calcareous. Forams observed.	2	0	0	0	0	0	0	0	0	X
1750'	1½	1	Sand, olive black, predominantly fine to lower medium, silty, well sorted, loosely consolidated slightly calcareous, est. fair porosity, poor permeability.	3	0	0	0	0	0	0	0	0	X
1800'	1 3/4	1	Sand, as above, predominantly very fine to upper fine, silty, common carbonaceous fragments	3	0	0	0	0	0	0	0	0	X
1840'	1½	1	Sand, grayish black, predominantly very fine to upper fine, loosely consolidated, well sorted silty, water saturated, est. good porosity, fair permeability.	S	0	0	0	0	0	0	0	0	X
1910'	1 3⁄4	1	Sand, as above, slightly calcareous.	S	0	0	0	0	0	0	0	0	X
1960'	1½	1	Sand, as at 1840', slightly calcareous.	S	0	0	0	0	0	0	0	0	X
2010'	1½	1	Sand, as at 1840, light gray, slightly calcareous	S	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; S,85-100%. **See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
(SIDEWALL CORE REPORT)

Page 4 of 4

Date June 14, 1966
Type Sidewall Sampler CST-Conventional with extra long wires
Cores Examined By J. J. Stosur

Location Offshore, XX, Oreg. Rec.
Area [illegible]
Well OCS-P 075-1ET

DEPTH	REC.	RUN	DESCRIPTION	LITH.*	OIL SHOWS**								
							Sample Oil Fluor.			Cut		Summary	
					% Oil Stain	Hydrocarbon Odor	%	Inten.	Color	Color of Cut	Color of Cut Fluor.	Show No.	Show Symbol
2050'	1½	1	Sand, as at 1840', moderately sorted, silty	S	0	0	0	0	0	0	0	0	X
2085'	13/4	1	Silt/Clay, soft to firm, common microbiotite, occasionally sandy, slightly calcareous, olive gray to olive black.	C	0	0	0	0	0	0	0	0	X
2105'	1½	1	Sand, as at 1840, slightly silty, subangular.	S	0	0	0	0	0	0	0	0	X
2120	1½	1	Sand, medium gray, very fine to lower fine, well sorted loosely consolidated, biotite and olivene? present, noncalcareous.	S	0	0	0	0	0	0	0	0	X
2140	1½	1	Sand, as above, more silty, olive black to greenish black, very fine silty - moderate sorting Sampled for magnetic susceptibility.	S	0	0	0	0	0	0	0	0	X
2150'	1½	1	Sand, as above, (megafossil?), red minerals (garnets) common.	S	0	0	0	0	0	0	0	0	X
2180'	1½	1	Sand, as above, noncalcareous	S	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C, 0-5%; 1, 5-30%; 2, 30-65%; 3, 65-95%; S, 95-100%.

**See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION

SIDEWALL CORE RECORD

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER S[illegible] GM.

Cores Examined By G. M. VALENTINE

Section ___ Twp. ___ Rge. ___ [illegible]

Area or Field STILT

Well SHELL P 075-1ET

DEPTH	REC.	RUN	DESCRIPTION	LITH.*	OIL SHOWS**								
							Sample Oil Fluor.			Cut		Summary	
			SHOT 60 SAMPLES, RECOVERED 57 SAMPLES 2 NO RECOVERY, 1 LOST BULLET.		% Oil Stain	Hydrocarbon Odor	%	Inten.	Color	Color of Cut	Color of Cut Fluor.	Show No.	Show Symbol
2280	2"	2	SILT - Olive black, sandy, soft, minor micaceous, carbonaceous fragments, forams observed.	1	0	0	0	0	0	0	0	0	X
2300	1½"	2	SAND - Olive gray to olive black, very fine, fair sorting, soft to unconsolidated, abundant shell hash. (P & P).	S	0	0	0	0	0	0	0	0	X
2350	2"	2	SILT - Olive gray, laminated, easily friable. Small megafossils and forams.	C	0	0	0	0	0	0	0	0	X
2400	1½"	2	SILT - Olive gray to light gray, friable, scattered, very fine sand grains. common megafossil fragments.	C	0	0	0	0	0	0	0	0	X
2480	13/4	2	SHALE - Silty, olive gray to olive black, friable, abundant megafossil fragments.	1	0	0	0	0	0	0	0	0	X
2530	1½"	2	SAND - Olive black, fine to very fine, soft to unconsolidated grains subangular, mostly quartz with 10% dark grains.	S	0	0	0	0	0	0	0	0	X
2570	1½"	2	SAND - as above at 2530'. Some garnet & mag. grains	S	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C, 0-5%; 1, 5-30%; 2, 30-65%; 3, 65-95%; S, 95-100%.

**See Legend for Oil Shows (over)

-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
[illegible]

Page -2-

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ___ Twp. ___ Rge. ___ [illegible]

Area or Field STILT

Well SHELL P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	% Oil Stain	% Hydrocarbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Intens.	Sample Oil Fluor. Color	Cut Color of Cut	Cut Color of Cut Fluor.	Summary Show No. Avg.	Summary Show Symb.
2630	0	2	Not recovered	C	0	0	0	0	0	0	0	0	X
2670	1 3/4	2	SILT - light olive gray, mass., easily friable, common fine micaceous.	S	0	0	0	0	0	0	0	0	X
2697	1"	2	SAND - Olive gray, fine to very fine, fair sorting unconsolidated to soft, subangular grains	S	0	0	0	0	0	0	0	0	X
2725	1½"	2	SAND - Olive black, fine, fair sorting, subrounded grains, common dark grains.	S	0	0	0	0	0	0	0	0	X
2766	1 3/4	2	SAND - As at 2725' but very fine, some silt-size grains.	S	0	0	0	0	0	0	0	0	X
2775	1½"	2	SAND - Olive gray to olive black. Very fine silty as at 2766.	3	0	0	0	0	0	0	0	0	X
2860	1½"	2	SAND - As at 2725. Multicolored grains.	S	0	0	0	0	0	0	0	0	X
2902	1½"	2	SILTSTONE - Olive gray, massive, friable, micaceous, common carbonaceous fragments.	C	0	0	0	0	0	0	0	0	X
2915	1½"	2	SAND - Olive gray to olive black, fine grained with some medium grains, [illegible] sorting, subrounded grains loosely consolidated. ([illegible])	S	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-50%; 3,50-85%; S,85-100%.

**See Legend for Oil Shows (over)

-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
[illegible]

Page -3-

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ___ Twp. ___ Rge. ___ [illegible]

Area or Field STILT

Well SHELL P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	% Oil Stain	% Hydrocarbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Intens.	Sample Oil Fluor. Color	Cut Color of Cut	Cut Color of Cut Fluor.	Summary Show No. Avg.	Summary Show Symb.
2976	1 3/4	2	SHALE - Olive gray, mass., friable, micro-micaceous, red and black minerals.	C	0	0	0	0	0	0	0	0	X
3030	1½"	2	SAND - Olive gray, very fine, silty, salt & pepper appearance. Carbonaceous fragments with some brown	S	0	0	0	0	0	0	0	0	X
3095	1½"	2	SAND - As at 2725'.	S	0	0	0	0	0	0	0	0	X
3107	1½"	2	SILTSTONE - Olive gray, mass., friable, trace of carbonaceous material	C	0	0	0	0	0	0	0	0	X
3150	1½"	2	SAND - Olive gray, very fine to silty, loosely consolidated	S	0	0	0	0	0	0	0	0	X
3200	1½"	2	SILT - Sandy, olive gray, common megafossil fragments, easily friable.	1	0	0	0	0	0	0	0	0	X
3228	1½"	2	SILT - Light olive gray, laminated, clay lenses. Very fine quartz grains in silt.	C	0	0	0	0	0	0	0	0	X
3235	1½"	2	SAND - Olive black, very fine to fine, as at 2725'.	S	0	0	0	0	0	0	0	0	X

3277	1¾	2	SHALE - Olive gray, massive, friable, micaceous, common forams.	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; S,85-100%. **See Legend for Oil Shows (over)

LM-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION

SIDEWALL CORE [illegible]

Page -4-

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. V[illegible]NTINE

Section ___ Twp. ___ Rge. ___ S.B.B.&M. M.D.B.&M.

Pool or Field STILT

Well SHELL P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH	OIL SHOWS**								
					% Oil Stain	Hydrocarbon Odor	Sample Oil Fluor. %	Inten.	Color	Color of Cut	Color of Cut Fluor.	Show No. Avg.	Show Symb.
3402	1"	2	SHALE - Olive gray, with [illegible] silt, easily friable, red, [illegible] & black [illegible]. Occasional forams.	1	0	0	0	0	0	0	0	0	X
3450	1½"	2	SILTSTONE - Olive gray, [illegible], easily friable, scattered very fine sand grains. Micro-calcareous scattered forams.	1	0	0	0	0	0	0	0	0	X
3510	1½"	2	SHALE - Olive gray as at 3402'.	C	0	0	0	0	0	0	0	0	X
3550	1¼"	2	SAND - Olive black, very fine-fine, soft, loosely consolidated. Fair sorting, multicolored grains (P & P).	S	0	0	0	0	0	0	0	0	X
3633	1¼"	2	SHALE - As at 3402'.	C	0	0	0	0	0	0	0	0	X
3660	1¼"	2	SAND - Olive black, very fine, silty, sorted moderate shell fragments, [illegible] dark grains and carbonaceous.	S	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; S,85-100%. **See Legend for Oil Shows (over)

LM-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION

SIDEWALL CORE [illegible]

Page -5-

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ___ Twp. ___ Rge. ___ S.B.B.&M. M.D.B.&M.

Pool or Field STILT

Well SHELL P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	OIL SHOWS**								
							Sample Oil Fluor.			Cut		Summary	
					% Oil Stain	Hydrocarbon Odor	%	Inten.	Color	Color of Cut	Color of Cut Fluor.	Show No. Avg.	Show Symb.
3722	2"	2	SHALE - Olive black, laminated, slightly silty, organic?	C	0	0	0	0	0	0	0	0	X
3775	1¼"	2	SILTSTONE - Olive gray, clayey, friable, micro-calcareous, massive.	C	0	0	0	0	0	[illegible]	0	0	X
3800	1¼"	2	SHALE - Light olive gray, very silty, micro-micaceous, massive.	C	0	0	0	0	0	0	0	0	X
310	1¼"	2	SHALE - Medium dark gray, massive, friable, minor silt.	C	0	0	0	0	0	0	0	0	X

3820	0	2	Not recovered										
3925	1¼"	2	SHALE - Light olive gray, laminated, laminae of 1 mm thickness	C	0	0	0	0	0	0	0	0	X
3978	1¼"	2	SILTSTONE - Clayey, olive black, massive, hackly, common forams, slickensided.	C	0	0	0	0	0	0	0	0	X
3985	1¼"	2	CLAY - Medium gray, bluish, massive, soft, unctuous.	C	0	0	0	0	0	0	0	0	X
4030	1¼"	2	CLAY SHALE - as at 3985' but partly laminated.	C	0	0	0	0	0	0	0	0	X
4100	1½"	2	SHALE - Olive gray, massive, easily friable, silty, micro-micaceous.	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-65%; 3,65-95%; S,95-100%.

**See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
SIDEWALL CORE RECORD

Page -6-

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ____ Twp. ____ Rge. ____ S.B.B.&M. / M.D.B.&M.

Area or Field STILT

Well SHELL P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH*	% Oil Stain	Hydro-carbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Cut Color of Cut	Cut Color of Cut Fluor.	Summary Show No. Avg.	Summary Show Symb.
4110	1¼"	2	SILTSTONE - Medium gray, friable, well sorted silt, some scattered very fine sand grains.	C	0	0	0	0	0	0	0	0	X
4185	1"	2	SHALE - as at 3985'	C	0	0	0	0	0	0	0	0	X
4202	1"	2	SHALE - Medium gray, laminated, very soft, micro-micaceous.	C	0	0	0	0	0	0	0	0	X
4250	1¼"	2	SILTSTONE - Olive gray, micaceous, micro-micaceous forams	C	0	0	0	0	0	0	0	0	X
4270	1¼"	2	SHALE - Medium gray, laminated, with low angle fractures (minor)	C	0	0	0	0	0	0	0	0	X
4325	1"	2	SHALE - Olive gray, easily friable, unctuous., slightly silty	C	0	0	0	0	0	0	0	0	X
4350	1¼"	2	SILTSTONE - Olive black, clayey, massive.	C	0	0	0	0	0	0	0	0	X
4365	1½"	2	SILTSTONE - as at 4350'	C	0	0	0	0	0	0	0	0	X
4395	1¼"	2	SHALE - dark gray, clayey, abundant small silt-filled borings	C	0	0	0	0	0	0	0	0	X
4425	1"	2	SHALE - Medium gray, easily friable, unctuous, massive.	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-65%; 3,65-95%; S,95-100%.

**See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
SIDEWALL CORE RECORD

Page -7-

Date 6-21-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ____ Twp. ____ Rge. ____ S.B.B.&M. / M.D.B.&M.

Area or Field STILT

Well SHELL P 0[illegible]-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	OIL SHOWS**								
					% Oil Stain	Hydrocarbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Cut: Color of Cut	Cut: Color of Cut Fluor.	Show No.	Show [illegible]
4480	1"	2	SHALE - Dark gray, massive, soft conchoidal fractures	C	0	0	0	0	0	0	0	0	X
4495	1"	2	SHALE - Medium gray, silty, soft	C	0	0	0	0	0	0	0	0	X
4550	1"	2	SH[illegible] - Olive gray, some thin laminated, unctuous, soft	C	0	0	0	0	0	0	0	0	X
4600	1"	2	SILTSTONE - Olive gray, massive, churned, easily friable	C	0	0	0	0	0	0	0	0	X
4650			Lost Bullet In Formation										
4700	1"	2	SILTSTONE - Olive gray, massive, easily friable	C	0	0	0	0	0	0	0	0	X
4755	1"	2	SHALE - Olive black, massive, unctuous.	C	0	0	0	0	0	0	0	0	X
4785	1"	2	SHALE - medium gray to olive gray, laminated	C	0	0	0	0	0	0	0	0	X
4800	1"	2	SHALE - Medium gray to dark gray, laminated or close-spaced micro-fractu	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-65%; 3,65-95%; S,95-100%. **See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION
[illegible]

Date 7-5-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined by G. M. [illegible]

Section ___ Twp. ___ Rge. ___ SBB&M. MDB&M.

Area or Field [illegible]

Well [illegible]

DEPTH	REC	RUN	DESCRIPTION	LITH SYM*	OIL SHOWS**								
					% Oil Stain	Hydrocarbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Cut: Color of Cut	Cut: Color of Cut Fluor.	Show No.	Show [illegible]
4838	0	3	Run #3: Shot 87 conventional bullets with extra long wires. Recovered 72, (3 No recovery, 5 pulled off, 7 [illegible]). PULLED OFF										
4900	1"	3	SHALE, Medium gray, Friable with different [illegible] on silt-filled borings.	C	0	0	0	0	0	0	0	0	X
4950	1¼	3	SHALE, medium gray, silty, [illegible], friable	C	0	0	0	0	0	0	0	0	X
4990	1½	3	MUDSTONE, silty, olive gray to olive black, some mica, forms unctuous.	C	0	0	0	0	0	0	0	0	X
5000	1½	3	MUDSTONE, olive gray, massive, silty, friable, unctuous.	C	0	0	0	0	0	0	0	0	X
5100	1"	3	SHALE, Medium gray, silty, micro-micaceous, friable massive.	C	0	0	0	0	0	0	0	0	X
5195	1¼	3	MUDSTONE, Olive gray, silty, massive, unctuous, friable.	C	0	0	0	0	0	0	0	0	X
5260	1½	3	CLAYSTONE, Medium gray, friable, micro-micaceous, massive.	C	0	0	0	0	0	0	0	0	X
5345	1½	3	MUDSTONE, Olive gray, silty, micro-micaceous, massive.	C	0	0	0	0	0	0	0	0	X
5438	1¼	3	SILTSTONE, Olive gray, clayey, massive, micro-micaceous.	C	0	0	0	0	0	0	0	0	X
5474	1"	3	SILTSTONE & CLAYSTONE [illegible]. Siltstone is light olive gray, [illegible], friable [illegible] [illegible]ility	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-65%; 3,65-95%; S,95-100%. **See Legend for Oil Shows (over)

LMI-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION

SIDEWALL CORE RECORD

Page -2-

Date 7-5-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ____ Twp. ____ Rge. ____ SBB.&M. MDB.&M.

Area or Field STILT

W. H. P 075-1ST

DEPTH	REC	RUN	DESCRIPTION	LITH SYM.*	% Oil Stain	Hydro-carbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Cut Color of Cut	Cut Color of Cut Fluor.	Summary Show No. Avg.	Summary Show Type
5474 (Continued)			loosely consolidated, claystone is olive gray, soft	C	0	0	0	0	0	0	0	0	X
5585	0	3	PULLED OFF										
5685	1½	3	MUDSTONE, olive gray to olive black, silty, massive, micaceous	C	0	0	0	0	0	0	0	0	X
5830	0	3	PULLED OFF	-									
5945	0	3	PULLED OFF	-									
6000	1½	3	SILTSTONE, light olive gray, clayey, faintly laminated, friable.	C	0	0	0	0	0	0	0	0	X
6065	1½	3	MUDSTONE, light olive gray, silty, massive, friable	C	0	0	0	0	0	0	0	0	X
6245	0	3	MISFIRE	-									
6380	1½	3	MUDSTONE, olive black, silty, fractures friable, massive	C	0	0	0	0	0	0	0	0	X
6412	1	3	CLAYSTONE, dark gray, massive, silty, micaceous	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; 5,85-100%.

**See Legend for Oil Shows (over)

LMI-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION

SIDEWALL CORE RECORD

Page -3-

Date 7-5-66

Type Sidewall Sampler SCHLUMBERGER - SOFT FM.

Cores Examined By G. M. VALENTINE

Section ____ Twp. ____ Rge. ____ SBB.&M. MDB.&M.

Area or Field STILT

W.H. P 075-1ST

DEPTH	REC	RUN	DESCRIPTION	LITH SYM.*	% Oil Stain	Hydro-carbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Inten.	Sample Oil Fluor. Color	Cut Color of Cut	Cut Color of Cut Fluor.	Summary Show No. Avg.	Summary Show Type
6450	0	3	MISFIRE	-									
6500	1 3/4	3	CLAYSTONE, olive black, massive, micaceous, soft										
6550	1½	3	CLAYSTONE, olive gray, bedded, unctuous, soft micaceous	C	0	0	0	0	0	0	0	0	X
6590	1½	3	SHALE, olive black, unctuous, bedded, soft [illegible] lant forms.	C	0	0	0	0	0	0	0	0	X
6660	1½	3	CLAYSTONE, olive black, unctuous, soft, massive, chalky shell fragments?	C	0	0	0	0	0	0	0	0	X

6750	13/4		SILTSTONE & CLAYSTONE [illegible]. Siltstone, olive grey, sorted, friable, claystone, olive black, unctuous, soft. Bedding 10° to [illegible].	C	0	0	0	0	0	0	0	0	X
6855	0	3	MISFIRE	-									
6950	1½	3	SILTSTONE, Clayey, olive grey, massive, soft, gritty	C	0	0	0	0	0	0	0	0	X
7050	1½	3	SHALE, olive black, silty, poor bedding, firm abundant forams	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; 5,85-100%.

See Legend for Oil Shows (over)

EM-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION

SIDEWALL CORE RECORD

Page -4-

Date 7-5-66

Section ______ Twp. ______ Rge. ______

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Area or Field STILT

Cores Examined By G. M. VALENTINE

Well P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH. SYMB.*	OIL SHOWS								
					% Oil Stain	Hydro-carbon Odor	Sample Oil Fluor.			Cut		Summary	
							%	Inten.	Color	Color of Cut	Color of Cut Fluor.	Show No.	Show Symb.
7160	1½	3	MUDSTONE, olive black, massive, firm common forams.	C	0	0	0	0	0	0	0	0	
7250	2	3	MUDSTONE, olive black, silty, massive, firm.	C	0	0	0	0	0	0	0	0	X
7350	13/4	3	SHALE, olive black, bedded, silty, common forams	C	0	0	0	0	0	0	0	0	X
7450	1½	3	SHALE, olive black as above at 7350	C	0	0	0	0	0	0	0	0	X
7550	3/4	3	SHALE as above at 7350	C	0	0	0	0	0	0	0		X
7650	1½	3	SHALE, olive black to brownish black as at 7350	C	0	0	0	0	0	0	0	0	X
7750	2		SHALE, as at 7350	C	0	0	0	0	0	0	0	0	X
7800	13/4	3	CLAYSTONE, olive black, massive, unctuous, friable, common forams.	C	0	0	0	0	0	0	0	0	X
7850	"	3	CLAYSTONE as at 7800 but fractures abundant [illegible] slicks.	C	0	0	0	0	0	0	0	0	X
7858	1½	3	CLAYSTONE as at 7850'.	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-30%; 2,30-55%; 3,55-85%; 5,85-100%.

See Legend for Oil Shows (over)

EM-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION

SIDEWALL CORE RECORD

Page -5-

Date 7-5-66

Section ______ Twp. ______ Rge. ______

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Area or Field STILT

Cores Examined By G. M. VALENTINE

Well P 075-1ET

DEPTH	REC.	RUN	DESCRIPTION	LITH SYM.*	OIL SHOWS**								
							Sample Oil Fluor.			Cut		Summary	
					% Oil Stain	Hydrocarbon Odor	%	Intens.	Color	Color of Cut	Color of Cut Fluor.	Show No. Avg.	Show Symb.
7900	2	3	CLAYSTONE as at 7850'.	C	0	0	0	0	0	0	0	0	X
7915	1½"	3	CLAYSTONE, as at 7850', micro-brecciated	C	0	0	0	0	0	0	0	0	X
7930	1½"	3	CLAYSTONE, as at 7850', micro-brecciated	C	0	0	0	0	0	0	0	0	X
7950	3/4	3	CLAYSTONE, as at 7850'.	C	0	0	0	0	0	0	0	0	X
7975	1½	3	CLAYSTONE, olive black, sectile, soft, gougy, white marbling.	C	0	0	0	0	0	0	0	0	X
8000	1½	3	CLAYSTONE, gougy as at 7975'	C	0	0	0	0	0	0	0	0	X
8050	1¾	3	CLAYSTONE, olive black, sectile, massive, fractur	C	0	0	0	0	0	0	0	0	X
8075	0	3	No Recovery	C	0	0	0	0	0	0	0	0	X
8150	1½	3	CLAYSTONE, as at 8050'	C	0	0	0	0	0	0	0	0	X
8175	1½	3	CLAYSTONE, as at 8050'	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-50%; 2,50-65%; 3,65-85%; S,85-100%.

**See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION
SIDEWALL CORE RECORD

Page -6-

Date 7-5-66

Section ____ Twp. ____ Rge. ____

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Area or Field STILT

Cores Examined By G. M. VALENTINE

Well P 075-1ET

DEPTH	REC.	RUN	DESCRIPTION	LITH SYM.*	OIL SHOWS**								
							Sample Oil Fluor.			Cut		Summary	
					% Oil Stain	Hydrocarbon Odor	%	Intens.	Color	Color of Cut	Color of Cut Fluor.	Show No. Avg.	Show Symb.
8250	1½	3	CLAYSTONE, olive black, massive, sectile, firm, abundant slicks.	C	0	0	0	0	0	0	0	0	X
8350	0	3	No Recovery	-									
8450	1½	3	CLAYSTONE, olive black, massive, sectile, slightly silty, forams observed	C	0	0	0	0	0	0	0	0	X
8550	1½	3	CLAYSTONE, as at 8450'. Large megafossil fragments	C	0	0	0	0	0	0	0	0	X
8650	0	3	No Recovery	-									
8750	1¼	3	CLAYSTONE, as at 8450'	C	0	0	0	0	0	0	0	0	X
8850	2	3	CLAYSTONE, as at 8450'	C	0	0	0	0	0	0	0	0	X
8915	1	3	CLAYSTONE, as at 8450'	C	0	0	0	0	0	0	0	0	X
9000	1¼	3	CLAYSTONE, as at 8450, common large bathysyphons?	C	0	0	0	0	0	0	0	0	X
9100	1½	3	CLAYSTONE, light olive gray, very silty, scattered fine sand grains, sheared, soft.	-									

*Lith. Symbol, % sand: C,0-5%; 1,5-50%; 2,50-65%; 3,65-85%; S,85-100%.

**See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
(SIDEWALL CORE RECORD)

Page -7-

Date 7-5-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ___ Twp. ___ Rge. ___ [illegible]

Area or Field STILT

Well P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM.*	% Oil Stain	Hydro-carbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Intsn.	Sample Oil Fluor. Color	Cut: Color of Cut	Cut: Color of Cut Fluor.	Summary: Show No. Avg.	Summary: Show Symb.
9200	½	3	GOUGE, olive black, soft, unctuous	C	0	0	0	0	0	0	0	0	X
9300	3/4	3	CLAYSTONE, olive gray, silty, vitreous, sheared, marbled with white streaks.	C	0	0	0	0	0	0	0	0	
9410	1	3	CLAYSTONE, olive black, easily friable, massive, sectile, minor fractures.	C	0	0	0	0	0	0	0	0	X
9430	13/4	3	CLAYSTONE, olive gray, silty, massive, easily friable	C	0	0	0	0	0	0	0	0	X
55	1	3	SILTSTONE, light olive gray, friable, massive 1/8" calcite veinlet or crushed megafossil frag.	C	0	0	0	0	0	0	0	0	X
9500	1½	3	SILTSTONE, greenish gray, massive, sandy, firm	C	0	0	0	0	0	0	0	0	X
95[illegible]	1½	3	MUDSTONE, olive gray, silty, massive firm	C	0	0	0	0	0	0	0	0	
9572	1½	3	SILTSTONE, olive gray, massive, firm	C	0	0	0	0	0	0	0	0	X
9600	1½	3	SILTSTONE, as at 9572'. Minor thin calcite streaks	C	0	0	0	0	0	0	0	0	X
9620	1½	3	SILTSTONE, olive gray, slightly sandy, massive, firm thin calcite veinlets	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C, 0-5%; 1, 5-30%; 2, 30-55%; 3, 55-85%; 4, 85-100%.

* See Legend for Oil Shows (over)

[illegible]-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
MARINE DIVISION
(SIDEWALL CORE RECORD)

Page -8-

Date 7-5-66

Type Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ___ Twp. ___ Rge. ___ [illegible]

Area or Field STILT

Well P 075-1ET

DEPTH	REC	RUN	DESCRIPTION	LITH SYM.	% Oil Stain	Hydro-carbon Odor	Sample Oil Fluor. %	Sample Oil Fluor. Intsn.	Sample Oil Fluor. Color	Cut: Color of Cut	Cut: Color of Cut Fluor.	Summary: Show No. Avg.	Summary: Show Symb.
9655	1	3	SILTSTONE, dark gray, clayey, with scattered large rounded sand grains and glauconite, massive	C	0	0	0	0	0	0	0	0	X
9690	½	3	CLAYSTONE, olive gray, fractured, massive, common pyrite veinlets, friable	C	0	0	0	0	0	0	0	0	X
9742	1	3	CLAYSTONE, brownish black, soft sheared to flaky texture	C	0	0	0	0	0	0	0	0	X

9732	0	3	MISFIRE	.								
9818	1½	3	CLAYSTONE, olive black, massive, gritty, common volcanic granules up to 0.2 inches	C	0	0	0	0	0	0	0	0	0
9845	½	3	VOLCANIC, greenish olive black, granular, friable palagoniticextrusive	-								
9887	0	3	MISFIRE	-								
9915	0	3	P[illegible]D OFF.	-								
9925	½	3	CLAYSTONE, olive black to greenish black, composed largely of altered basaltic debris, cut by 1/8" calcite veinlets.	-								

*Lith. Symbol, % sand: C,0-5%; 1,5-35%; 2,35-65%; 3,65-95%; 3,95-100%. See Legend for Oil Shows (over)

EM-2749 (Rev. 9-62)
Printed in U.S.A.

SHELL OIL COMPANY
[illegible] DIVISION
[illegible]

Page -9-

Date 7-5-66

Type of Sidewall Sampler SCHLUMBERGER SOFT FM.

Cores Examined By G. M. VALENTINE

Section ____ Twp. ____ Rge. ____ [illegible]

Area or Field STILT

Well P 075-1ET

DEPTH	Rec.	Rec.	[illegible]	Lith. Sym.	% Oil Stain	% Hydrocarbon Odor	%	Intens.	Color	Color of Cut	Color of Cut Fluor.	[illegible] No. Avg.	Show Symbol
9975.	0	3	MISFIRE	--									
10,008	½	3	VOLCANIC, grayish black, friable, palagonitic, zeolitic	-									
10,040	½	3	VOLCANIC, greenish gray, crystalline, friable.	-									
10,060	0	3	MISFIRE	-									
10,075	½	3	VOLCANIC, greenish black, crystalline, palogonitic, calcite veinlets, pyrite	-									
10,080	½	3	VOLCANIC, as at 10,075	-									
10,103	½	3	VOLCANIC, dark gray, soft, mush palagonitic, [illegible]ered.	-									
10,108	½	3	VOLCANIC, grayish black, friable, zeolitic, palagonitic. May be partly cemented	-									
10,118	½	3	SHALE, black baked? in hard brittle fragments	C	0	0	0	0	0	0	0	0	X

*Lith. Symbol, % sand: C,0-5%; 1,5-35%; 2,35-65%; 3,65-95%; 3,95-100%. See Legend for Oil Shows (over)