

Bore Hole Impenetrated Sonre Log  
 1-11-52  
 100

COUNTY OFFSHORE  
 FIELD & LOCATION W. PART BAR  
 WELL 9-4-65 - P 597-2ET

COMPANY SHELL OIL COMPANY  
 FIELD OFFSHORE  
 WELL 9-4-65 - P 597-2ET - TERMINATED

COMPANY WELL 9-4-65  
 LOCATION OFFSHORE NEAR BAR STATE OREGON  
 COUNTY OFFSHORE  
 LOCATION (optional) MAP #2 AREA 15A NO. 15  
X = 15, 2, 478 Y = 281, 785  
 Other Services: 500  
500  
500  
 Sec. 1 1 1 1  
 Twp. 1 1 1 1  
 Rgn. 1 1 1 1

Permanent Datum: Station 114 Elev. 292  
 Log Measured From: 0 Fi. Above Perm. Datum  
 Drilling Measured From: 0 Fi. Above Perm. Datum  
 Elev.: K.B. 66  
 G.L. 66

Date: 9-4-65  
 Run No.: 2  
 Depth-Driller: 4192  
 Depth-Logger: 4178  
 Rim Log Interval: 4178  
 Casing-Driller: 134 @ 2857  
 LOP Log Interval: 134 @ 2857  
 Casing-Logger: 134 @ 2857  
 Bit Size: 10 1/4 with 1 1/4 hole gauges  
 Type Fluid in Hole: Oil emulsion  
 Dens. Visc. 0.52 60 ml  
 pH Fluid Loss 9.5 78 ml  
 Source of Sample: Flowline OF  
 R. @ Meas. Temp. 43 @ 28 OF  
 R. @ Meas. Temp. 43 @ 28 OF  
 R. @ Meas. Temp. 43 @ 28 OF  
 Source: Rm. Rm. 7 7 OF  
 R. @ BHT 7 7 OF  
 R. @ BHT 7 7 OF  
 Time Since Circ. 114 hr. of  
 Max. Rec. Temp. 114 hr. of  
 Equip. Location C60 3NC  
 Recorded by ANDREVA  
 Witnessed by ANDREVA

REMARKS *Not to be reproduced without written permission Schlumberger Well Servicing Corporation*

Changes in Mud Type or Additional Samples		Scale Changes		
Date	Sample No.	Type Log	Depth	Scale Up Hole
Depth-Driller				
Type Fluid in Hole				
Dens.	Visc.			
ph	Fluid Loss	ml		
Source of Sample				
R. @ Meas. Temp.	R. @ Meas. Temp.	Run No.	Tool Type	Tool Position
R. @ Meas. Temp.	R. @ Meas. Temp.	<u>1</u>	<u>B5L</u>	<u>Centered</u>
R. @ Meas. Temp.	R. @ Meas. Temp.			
Source: Rm. Rm.				
R. @ BHT	R. @ BHT			
R. @ BHT	R. @ BHT			
R. @ BHT	R. @ BHT			

C.D.: Used S.O.: SAC A166  
 Equip. Used: CART. No. SAC A166  
 PANEL No. SAC A166  
 SONDE No. SLS A179

Velocity (feet per second) =  $\frac{1,000,000}{\text{Interval Transit Time (microseconds per foot)}}$

SPONTANEOUS-POTENTIAL /100 MILLIVOLTS	DEPTHS	INTERVAL TRANSIT TIME MICROSECONDS PER FOOT	
		75	75
<u>-10</u>		<u>175</u>	<u>165</u>
<b>CALIPER</b> HOLE DIAM. IN INCHES			
<u>6"</u>			
<u>16"</u>			

