

WELL SUMMARY REPORT  
 (Submit in duplicate)

Operator R. A. Stamey Field Sand Hollow Area

Well No. Russell 1 NW1/4 Sec. 14, T 19S, R 14E, WM W. B. & M.

Location 330' S & 330' E from NW corner Elevation above sea level 2290' feet

All depth measurements taken from top of Kelly Bushing, which is 2297' feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date 1954 Signed R. A. Stamey

Engineer or Geologist \_\_\_\_\_ Superintendent \_\_\_\_\_ Title President  
 (President, Secretary or Agent)

Commenced drilling June 11, 1954 Completed drilling July 25, 1958 Drilling tools Cable Rotary

Total depth 4336' Plugged depth \_\_\_\_\_ GEOLOGICAL MARKERS DEPTH

Junk \_\_\_\_\_ Pliocene lacustrine 0-4336'  
seds pyroclastics  
and volc flows

Commenced producing \_\_\_\_\_ Date \_\_\_\_\_ Flowing/gas lift/pumping  
 (cross out unnecessary words)

Initial production  
 Production after 30 days

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure

CASING RECORD (Present Hole)

Size of casing (A.P.L.)	Depth of shoe	Top of casing	Weight of casing	New or sec- ond hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cement- ing if through perforations
10 3/4"	216'	0					12 1/4"	138 sacks	Around shoe

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				