

RECORDED
NOV 1 1960
STATE DEPT. OF GEOLOGY & MINERAL INDUSTRIES

WELL SUMMARY REPORT
(Submit in duplicate)

Operator Humble Oil & Refining Company Field Thomas Creek Area
Well No. Thomas Creek Unit Block Sec. 18, ^{III Well #1} T36-S, R 18-E, W. B. & M.
Location 2240' N & 925' W of SE 1/4 of NE 1/4 Elevation above sea level 5260 feet
All depth measurements taken from top of Kelly Drive Bushing, which is 16 feet above ground

In compliance with the rules and regulations pursuant to ORS 520 (Chapter 667 OL 1953) the information given herewith is a complete and correct record of the present condition of the well and all work done thereon, so far as can be determined from all available records.

Date November 1, 1960 Signed James E. Cox
Engineer ~~OK K. K. K. K. K.~~ Superintendent Title District Superintendent
(~~President, Secretary or Agent~~)

Commenced drilling 7-20-60 Completed drilling 10-25-60 Drilling tools Cable Rotary
Total depth 12,093 Plugged depth Dry & Abandoned GEOLOGICAL MARKERS DEPTH
Junk 1 - 10-5/8" bit, 6 - 8" x 30' drill collars, Unknown
1 - crossover sub, 1 - pin off of 5" drill pipe,
1 - 9-5/8" overshot, 2 - crossover subs, 1 - set
of 5" Itco jars & barrel from bumper sub.

Commenced producing None Date None Flowing/gas lift/pumping
(cross out unnecessary words)

Clean oil bbl. per day	Gravity Clean oil	Percent water including emulsion	Gas Mcf. per day	Tubing Pressure	Casing Pressure
Initial production					
Production after 30 days					

CASING RECORD (Present Hole)

Size of casing (A.P.L)	Depth of shoe	Top of casing	Weight of casing	New or second hand	Seamless or Lapweld	Grade of casing	Size of hole drilled	No. of sacks of cement	Depth of cementing if through perforations
16"	1015	16	75 & 84	New	33	J-55	22"	800	

PERFORATIONS

Size of casing	From	To	Size of perforations	Number of rows	Distance between centers	Method of perforations
	ft.	ft.	None			
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				
	ft.	ft.				