Cement Bond Log
Variable Density

COMPANY	Carlton Energy International
WELL	'WNS Monasha' #32-1
FIELD	Wildcat
COUNTY	Coos
STATE	Oregon
API NUMBER	
LOCATION	
LATITUDE	
LONGITUDE	
SECTION	
TOWNSHIP	
RANGE	
PERMANENT DATUM	GL Elev. 0.00
LOG MEASURED FROM	KB 26.00 Above Perm. Datum
DRILLING MEASURED FROM	KB
Elev.: K.B.	26.00
D.F.	
G.L.	0.00
DATE	17-FEB-1994
RUN NUMBER	ONE
TD DRILLER	1500.00
TD LOGGER	1500.00
BTM. LOG INTERVAL	1500.00
TOP LOG INTERVAL	0.00
CASING - DRILLER	4.500 @ 0.00
CASING - LOGGER	0.00
BIT SIZE	6.250
TYPE FLUID IN HOLE	AIR
DENSITY / VISCOSITY	
PH / FLUID LOSS	
SOURCE OF SAMPLE	
RM @ MEASURED TEMPERATURE	
RMF @ MEASURED TEMPERATURE	
RMC @ MEASURED TEMPERATURE	
SOURCE: RMF / RMC	
RM @ BHT	
TIME SINCE CIRCULATION	
MAX. REC. TEMP.	
EQUIPMENT NO.	
LOCATION	
RECORDED BY	
WITNESSED BY	

THIS DATA IS PROVIDED IN ACCORDANCE WITH SCHLUMBERGER'S STANDARD TERMS AND CONDITIONS.
Schlumberger makes no representation or warranty of any kind, express or implied, regarding the accuracy, adequacy, completeness, legality, reliability or usefulness of any information furnished in connection with this document. In no event shall Schlumberger be liable for any direct, special or consequential damages.

Run No.	ONE
Service Order No.	80407
Logging Speed	3000 FT/HR
EQUIPMENT DATA	
Tool Number 1	CNL-B-1217
Tool Number 2	CSU-B-038
Tool Number 3	SGC-B-1545
Tool Number 4	CAL-B-1382
Tool Number 5	SLM-DB-1206
Tool Number 6	WBC-PB
Tool Number 7	
Tool Number 8	
Tool Number 9	
Tool Number 10	
Tool Number 11	
Tool Number 12	
REMARKS:	CEMENT BOND LOG RUN ON 17-FEB-1994

LOGGING TOOL STRING SKETCH

TOTAL TOOL STRING LENGTH IS 31.9 F
TOTAL TOOL STRING WEIGHT IS 500 LB IN AIR

Main Log - 0 psi



SENSOR MEASURE POINT TO TOOL ZERO

OTT	8.2 FEET	SOTE	30.5 FEET
SLTQ	8.2 FEET	CALB	34.2 FEET

PARAMETERS

PARAMETER	VALUE	UNIT
SMB - Sonic Memory Board	ALLO	
VDLE - Defs not found	21N	
TEQU - Defs not found	21N	
TGCA - TG Correction Status	DISA	
RATC - Firing Rate	15	HZ
DEC - Downhole Gain	220	
DETC - Detection	E1	
MMGC - Near Minimum Sliding Gate	220	US
CBLL - CBL Gate Width	20	US
AMPC - Sonic Amplitude	2	
CBC - Cement Bond Log Amplitude	UT	
WFM - Waveform Mode	MONO	
SS - Sonic Speed	0	
TDD - TD Delay	DISA	
DTM - Delta-T Field	189.000	US/F
DTR - Delta-T Matrix	56.0000	US/F
CSTS - Correction for Delta-T Shale, Empirical	100.000	
SPFS - Sonic Porosity Formula Select	0-S	
MRDO - Weight of Mud	8.5000	LB/G
WCIT - WCT Calibration Jig Type	CGR3	
CSTR - Compressive Strength of Cement	1000.00	PSIA
LSPC - Logging Speed	3000.00	LB/F
DMTC - Digitizer Word Count	512	
DSIN - Digitizer Sample Interval	5	US
DSDD - Digitizing Delay	300	US
BS - Bit Size	6.25000	IN
BDS - Borehole Status (Open or Cased)	CASE	
CSIZ - Casing Size	4.50000	IN

Repeat Section - 0 psi

SENSOR MEASURE POINT TO TOOL ZERO

OTT	8.2 FEET	SOTE	30.5 FEET
SLTQ	8.2 FEET	CALB	34.2 FEET

PARAMETERS

PARAMETER	VALUE	UNIT
SMB - Sonic Memory Board	ALLO	
VDLE - Defs not found	21N	
TEQU - Defs not found	21N	
TGCA - TG Correction Status	DISA	
RATC - Firing Rate	15	HZ
DEC - Downhole Gain	220	
DETC - Detection	E1	
MMGC - Near Minimum Sliding Gate	220	US
CBLL - CBL Gate Width	20	US
AMPC - Sonic Amplitude	2	
CBC - Cement Bond Log Amplitude	UT	
WFM - Waveform Mode	MONO	
SS - Sonic Speed	0	
TDD - TD Delay	DISA	
DTM - Delta-T Field	189.000	US/F
DTR - Delta-T Matrix	56.0000	US/F
CSTS - Correction for Delta-T Shale, Empirical	100.000	
SPFS - Sonic Porosity Formula Select	0-S	
MRDO - Weight of Mud	8.5000	LB/G
WCIT - WCT Calibration Jig Type	CGR3	
CSTR - Compressive Strength of Cement	1000.00	PSIA
LSPC - Logging Speed	3000.00	LB/F
DMTC - Digitizer Word Count	512	
DSIN - Digitizer Sample Interval	5	US
DSDD - Digitizing Delay	300	US
BS - Bit Size	6.25000	IN
BDS - Borehole Status (Open or Cased)	CASE	
CSIZ - Casing Size	4.50000	IN

COMPANY	Carlton Energy International	SCAL FB	0.0000
WELL	'WNS Monasha' #32-1	SCAL TB	0.0000
FIELD	Wildcat	DRUN TB	0.0000
COUNTY	Coos	Elev. KB	0.0000
STATE	Oregon	DF	0.0000
		GL	0.0000

Schlumberger