DATE	DEPTH	DETAILS OF OPERATION, DESCRIPTION & RESULTS
1-24-62	8427	Reamed. Ran 5 drill collars to bottom. Drilled 8427' to 8447'
1-25-62	8447	Drilled to 8447'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8427'-8447'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8447'-8000'. Pulled out of hole. Conditioned and circulated. Stripped out of hole. Ran core barrel.
1-26-62	8447	Rigged up and ran 12 pieces of 9-5/8" 36# 8-Rd API casing. Ran 8447' of drill pipe. Cemented 9-5/8" as follows: Pump 40 sacks cement, 20 sacks Class "G" with 10 sacks Class 50-50 with 2% Gel. Displacement 8447' with 1000 cu. ft. of water. Pressure up to 1000 psi. Circulating throughout.
1-26-62	8447	9-5/8" CASING DETAIL 1 9-5/8" Halliburton float shoe, 8-Rd 0.52 1 jt. 9-5/8" 36#, 8-Rd, STC, Set by 31.00 1 9-5/8" Cross-Over Sub 12 jts. 9-5/8" 36#, 8-Rd, STC, Set casing 398.00 Total casing run 431.52 Casing out off 3.00 Casing in hole 428.52 Stationary RM to casing head flange 12.00 BOTTOM DEPTH 440.52
1-26-62	8447	Installed 9-5/8" 8Rd x 10" 3M casinghead. Nipped up Hydrenol preventers. Tested blind rams and casing to 1000 psi, okay. Went in hole with 8½ bit. Drilled cement 400'-440'. Tested casing shoe to 1000 psi, okay. Drilled 8447'-8450'. Pulled out of hole. Ran core barrel. Reamed 8427'-8447'. Cored 8447'-8450'. Kimmel presentative was witnessed by Mr. Dennis Kimmel and Mr. Don Self of NMOCC.

DATE	DEPTH	DETAILS OF OPERATION, DESCRIPTION & RESULTS
1-27-62	8450	Pulled out of hole. Ran core barrel. Cored 8450'-8500'. Pulled out of hole. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8500'-8000'. Pulled out of hole. Ran core barrel. Reamed 8450'-8500'. Cored 8500'-8503'.
1-28-62	8503	Cored 8503'-8506'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8500'-8503'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8503'-8000'. Pulled out of hole. Ran core barrel. Reamed 8500'-8503'. Cored 8503'-8506'.
1-29-62	8506	Cored 8506'-8509'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8503'-8506'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8506'-8000'. Pulled out of hole. Ran core barrel. Reamed 8503'-8506'. Cored 8506'-8509'.
1-30-62	8509	Cored 8509'-8512'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8506'-8509'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8509'-8000'. Pulled out of hole. Ran core barrel. Reamed 8506'-8509'. Cored 8509'-8512'.
1-31-62	8512	Cored 8512'-8515'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8509'-8512'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8512'-8000'. Pulled out of hole. Ran core barrel. Reamed 8509'-8512'. Cored 8512'-8515'.
2-1-62	8515	Cored 8515'-8518'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8512'-8515'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8515'-8000'. Pulled out of hole. Ran core barrel. Reamed 8512'-8515'. Cored 8515'-8518'.
2-2-62	8518	Cored 8518'-8521'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8515'-8518'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8518'-8000'. Pulled out of hole. Ran core barrel. Reamed 8515'-8518'. Cored 8518'-8521'.
2-3-62	8521	Cored 8521'-8524'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8518'-8521'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8521'-8000'. Pulled out of hole. Ran core barrel. Reamed 8518'-8521'. Cored 8521'-8524'.
2-4-62	8524	Cored 8524'-8527'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8521'-8524'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8524'-8000'. Pulled out of hole. Ran core barrel. Reamed 8521'-8524'. Cored 8524'-8527'.
2-5-62	8527	Cored 8527'-8530'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8524'-8527'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8527'-8000'. Pulled out of hole. Ran core barrel. Reamed 8524'-8527'. Cored 8527'-8530'.
2-6-62	8530	Cored 8530'-8533'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8527'-8530'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8530'-8000'. Pulled out of hole. Ran core barrel. Reamed 8527'-8530'. Cored 8530'-8533'.
2-7-62	8533	Cored 8533'-8536'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8530'-8533'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8533'-8000'. Pulled out of hole. Ran core barrel. Reamed 8530'-8533'. Cored 8533'-8536'.
2-8-62	8536	Cored 8536'-8539'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8533'-8536'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8536'-8000'. Pulled out of hole. Ran core barrel. Reamed 8533'-8536'. Cored 8536'-8539'.
2-9-62	8539	Cored 8539'-8542'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8536'-8539'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8539'-8000'. Pulled out of hole. Ran core barrel. Reamed 8536'-8539'. Cored 8539'-8542'.
2-10-62	8542	Cored 8542'-8545'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8539'-8542'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8542'-8000'. Pulled out of hole. Ran core barrel. Reamed 8539'-8542'. Cored 8542'-8545'.
2-11-62	8545	Cored 8545'-8548'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8542'-8545'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8545'-8000'. Pulled out of hole. Ran core barrel. Reamed 8542'-8545'. Cored 8545'-8548'.
2-12-62	8548	Cored 8548'-8551'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8545'-8548'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8548'-8000'. Pulled out of hole. Ran core barrel. Reamed 8545'-8548'. Cored 8548'-8551'.
2-13-62	8551	Cored 8551'-8554'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8548'-8551'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8551'-8000'. Pulled out of hole. Ran core barrel. Reamed 8548'-8551'. Cored 8551'-8554'.
2-14-62	8554	Cored 8554'-8557'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8551'-8554'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8554'-8000'. Pulled out of hole. Ran core barrel. Reamed 8551'-8554'. Cored 8554'-8557'.

DATE	DEPTH	DETAILS OF OPERATION, DESCRIPTION & RESULTS
2-15-62	8557	Cored 8557'-8560'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8554'-8557'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8557'-8000'. Pulled out of hole. Ran core barrel. Reamed 8554'-8557'. Cored 8557'-8560'.
2-16-62	8560	Cored 8560'-8563'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8557'-8560'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8560'-8000'. Pulled out of hole. Ran core barrel. Reamed 8557'-8560'. Cored 8560'-8563'.
2-17-62	8563	Cored 8563'-8566'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8560'-8563'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8563'-8000'. Pulled out of hole. Ran core barrel. Reamed 8560'-8563'. Cored 8563'-8566'.
2-18-62	8566	Cored 8566'-8569'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8563'-8566'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8566'-8000'. Pulled out of hole. Ran core barrel. Reamed 8563'-8566'. Cored 8566'-8569'.
2-19-62	8569	Cored 8569'-8572'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8566'-8569'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8569'-8000'. Pulled out of hole. Ran core barrel. Reamed 8566'-8569'. Cored 8569'-8572'.
2-20-62	8572	Cored 8572'-8575'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8569'-8572'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8572'-8000'. Pulled out of hole. Ran core barrel. Reamed 8569'-8572'. Cored 8572'-8575'.
2-21-62	8575	Cored 8575'-8578'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8572'-8575'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8575'-8000'. Pulled out of hole. Ran core barrel. Reamed 8572'-8575'. Cored 8575'-8578'.
2-22-62	8578	Cored 8578'-8581'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8575'-8578'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8578'-8000'. Pulled out of hole. Ran core barrel. Reamed 8575'-8578'. Cored 8578'-8581'.
2-23-62	8581	Cored 8581'-8584'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8578'-8581'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8581'-8000'. Pulled out of hole. Ran core barrel. Reamed 8578'-8581'. Cored 8581'-8584'.
2-24-62	8584	Cored 8584'-8587'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8581'-8584'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8584'-8000'. Pulled out of hole. Ran core barrel. Reamed 8581'-8584'. Cored 8584'-8587'.
2-25-62	8587	Cored 8587'-8590'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8584'-8587'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8587'-8000'. Pulled out of hole. Ran core barrel. Reamed 8584'-8587'. Cored 8587'-8590'.
2-26-62	8590	Cored 8590'-8593'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8587'-8590'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8590'-8000'. Pulled out of hole. Ran core barrel. Reamed 8587'-8590'. Cored 8590'-8593'.
2-27-62	8593	Cored 8593'-8596'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8590'-8593'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8593'-8000'. Pulled out of hole. Ran core barrel. Reamed 8590'-8593'. Cored 8593'-8596'.
2-28-62	8596	Cored 8596'-8599'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8593'-8596'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8596'-8000'. Pulled out of hole. Ran core barrel. Reamed 8593'-8596'. Cored 8596'-8599'.
3-1-62	8599	Cored 8599'-8602'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8596'-8599'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8599'-8000'. Pulled out of hole. Ran core barrel. Reamed 8596'-8599'. Cored 8599'-8602'.
3-2-62	8602	Cored 8602'-8605'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8599'-8602'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8602'-8000'. Pulled out of hole. Ran core barrel. Reamed 8599'-8602'. Cored 8602'-8605'.
3-3-62	8605	Cored 8605'-8608'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8602'-8605'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8605'-8000'. Pulled out of hole. Ran core barrel. Reamed 8602'-8605'. Cored 8605'-8608'.
3-4-62	8608	Cored 8608'-8611'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8605'-8608'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8608'-8000'. Pulled out of hole. Ran core barrel. Reamed 8605'-8608'. Cored 8608'-8611'.
3-5-62	8611	Cored 8611'-8614'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8608'-8611'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8611'-8000'. Pulled out of hole. Ran core barrel. Reamed 8608'-8611'. Cored 8611'-8614'.
3-6-62	8614	Cored 8614'-8617'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8611'-8614'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8614'-8000'. Pulled out of hole. Ran core barrel. Reamed 8611'-8614'. Cored 8614'-8617'.
3-7-62	8617	Cored 8617'-8620'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8614'-8617'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8617'-8000'. Pulled out of hole. Ran core barrel. Reamed 8614'-8617'. Cored 8617'-8620'.

DATE	DEPTH	DETAILS OF OPERATION, DESCRIPTION & RESULTS
3-8-62	8620	Cored 8620'-8623'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8617'-8620'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8620'-8000'. Pulled out of hole. Ran core barrel. Reamed 8617'-8620'. Cored 8620'-8623'.
3-9-62	8623	Cored 8623'-8626'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8620'-8623'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8623'-8000'. Pulled out of hole. Ran core barrel. Reamed 8620'-8623'. Cored 8623'-8626'.
3-10-62	8626	Cored 8626'-8629'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8623'-8626'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8626'-8000'. Pulled out of hole. Ran core barrel. Reamed 8623'-8626'. Cored 8626'-8629'.
3-11-62	8629	Cored 8629'-8632'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8626'-8629'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8629'-8000'. Pulled out of hole. Ran core barrel. Reamed 8626'-8629'. Cored 8629'-8632'.
3-12-62	8632	Cored 8632'-8635'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8629'-8632'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8632'-8000'. Pulled out of hole. Ran core barrel. Reamed 8629'-8632'. Cored 8632'-8635'.
3-13-62	8635	Cored 8635'-8638'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8632'-8635'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8635'-8000'. Pulled out of hole. Ran core barrel. Reamed 8632'-8635'. Cored 8635'-8638'.
3-14-62	8638	Cored 8638'-8641'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8635'-8638'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8638'-8000'. Pulled out of hole. Ran core barrel. Reamed 8635'-8638'. Cored 8638'-8641'.
3-15-62	8641	Cored 8641'-8644'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8638'-8641'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8641'-8000'. Pulled out of hole. Ran core barrel. Reamed 8638'-8641'. Cored 8641'-8644'.
3-16-62	8644	Cored 8644'-8647'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8641'-8644'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8644'-8000'. Pulled out of hole. Ran core barrel. Reamed 8641'-8644'. Cored 8644'-8647'.
3-17-62	8647	Cored 8647'-8650'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8644'-8647'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8647'-8000'. Pulled out of hole. Ran core barrel. Reamed 8644'-8647'. Cored 8647'-8650'.
3-18-62	8650	Cored 8650'-8653'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8647'-8650'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8650'-8000'. Pulled out of hole. Ran core barrel. Reamed 8647'-8650'. Cored 8650'-8653'.
3-19-62	8653	Cored 8653'-8656'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8650'-8653'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8653'-8000'. Pulled out of hole. Ran core barrel. Reamed 8650'-8653'. Cored 8653'-8656'.
3-20-62	8656	Cored 8656'-8659'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8653'-8656'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8656'-8000'. Pulled out of hole. Ran core barrel. Reamed 8653'-8656'. Cored 8656'-8659'.
3-21-62	8659	Cored 8659'-8662'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8656'-8659'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8659'-8000'. Pulled out of hole. Ran core barrel. Reamed 8656'-8659'. Cored 8659'-8662'.

DATE	DEPTH	DETAILS OF OPERATION, DESCRIPTION & RESULTS
3-22-62	8662	Cored 8662'-8665'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8659'-8662'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8662'-8000'. Pulled out of hole. Ran core barrel. Reamed 8659'-8662'. Cored 8662'-8665'.
3-23-62	8665	Cored 8665'-8668'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8662'-8665'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8665'-8000'. Pulled out of hole. Ran core barrel. Reamed 8662'-8665'. Cored 8665'-8668'.
3-24-62	8668	Cored 8668'-8671'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8665'-8668'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8668'-8000'. Pulled out of hole. Ran core barrel. Reamed 8665'-8668'. Cored 8668'-8671'.
3-25-62	8671	Cored 8671'-8674'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8668'-8671'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8671'-8000'. Pulled out of hole. Ran core barrel. Reamed 8668'-8671'. Cored 8671'-8674'.
3-26-62	8674	Cored 8674'-8677'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8671'-8674'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8674'-8000'. Pulled out of hole. Ran core barrel. Reamed 8671'-8674'. Cored 8674'-8677'.
3-27-62	8677	Cored 8677'-8680'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8674'-8677'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8677'-8000'. Pulled out of hole. Ran core barrel. Reamed 8674'-8677'. Cored 8677'-8680'.
3-28-62	8680	Cored 8680'-8683'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8677'-8680'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8680'-8000'. Pulled out of hole. Ran core barrel. Reamed 8677'-8680'. Cored 8680'-8683'.
3-29-62	8683	Cored 8683'-8686'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8680'-8683'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8683'-8000'. Pulled out of hole. Ran core barrel. Reamed 8680'-8683'. Cored 8683'-8686'.
3-30-62	8686	Cored 8686'-8689'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8683'-8686'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8686'-8000'. Pulled out of hole. Ran core barrel. Reamed 8683'-8686'. Cored 8686'-8689'.
3-31-62	8689	Cored 8689'-8692'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8686'-8689'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8689'-8000'. Pulled out of hole. Ran core barrel. Reamed 8686'-8689'. Cored 8689'-8692'.
4-1-62	8692	Cored 8692'-8695'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8689'-8692'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8692'-8000'. Pulled out of hole. Ran core barrel. Reamed 8689'-8692'. Cored 8692'-8695'.
4-2-62	8695	Cored 8695'-8698'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8692'-8695'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8695'-8000'. Pulled out of hole. Ran core barrel. Reamed 8692'-8695'. Cored 8695'-8698'.
4-3-62	8698	Cored 8698'-8701'. Circulated and conditioned. Stripped out of hole. Ran core barrel and reamed 8695'-8698'. Circulated and conditioned. Pulled out of hole to top. Rigged up Halliburton. Ran DC-Sonic as follows: Sonic sondes, 1 foot spacing, 8 foot DC spacing, 1 foot spacing, DC sonde. Ran sonic log 8698'-8000'. Pulled out of hole. Ran core barrel. Reamed 8695'-8698'. Cored 8698'-8701'.
4-4-62	8701	Cored 8701'-8704'. Circulated and conditioned. Stripped out of hole. Ran core barrel and re