

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
910 State Office Building Portland, OR 97201

WELL SUMMARY REPORT

(In compliance with rules and regulations pursuant to ORS 520)

Amoco Production Co. (Company or operator) Weyerhaeuser B (Lease) 1 (Well No.)
 Sec. 13, T. 25 S, R. 9 W W.B. & M. Surveyed Coordinates: 811' FSL x
2859' FEL

Wildcat: X (or) Field Name: _____ County: Douglas
 Elevation of ground above sea level is 1430 feet. All depth measurements are taken from 1455'
 K.B. _____, which is 25' above ground.

Date: 5-20-85 Signature: BDS Shaw
 Position: Adm. Supervisor

Commenced drilling: 9-22-84 Completed drilling: 2-7-85 P&A: 2-7-85
 Total depth: 11330 Redrill depth: _____
 Logs run: Sonic, DLL, FDC-CNL-GR, CST, HDT

Size of hole	Size of casing	Wt. in lbs. per ft.	Grade Type	Depth	Amount of cement
42"	30"	157.53	B	98'	593 SX
26"	20"	94	K-55	1006'	700 SX
17-1/2"	13-3/8"	72 & 68	N-80	5766'	2888 SX

RECEIVED - PTLD
MAY 29 1985
 DEPT. OF GEOLOGY
 & MINERAL INDUSTRIES

Plugs	Geological Marker	Depth
6089' - 5785' 386 SX Class G	TYEE	Surface
5792' - 5666' 111 SX Class G	Flournoy	6412'
4520' - 4340' 130 SX Class G	Siletz River	6915'
XXXX 2784' - 2634' 470 SX Class G		
10' Surface		

Size of casing	From	To	Shots/ft.	Method of Perforating		
				Jet	Bullet	Slotted Liner
13-3/8	4440	4460	12	X		
13-3/8	3023	3025	4	X		
13-3/8	2948	2950	4	X		

Date	Clean Oil bbl/day	Gravity	Percent Water	Gas MMcf/day	F.T.P.	F.C.P.	S.I.T.P.	S.I.C.P.