

STATE OF OREGON
DEPARTMENT OF GEOLOGY AND MINERAL INDUSTRIES
702 Woodlark Building, Portland 5, Oregon

History of Oil or Gas Well

(Submit in duplicate)

To comply with Chapter 365 O.L. 1949.

Operator I. W. Love Drilling Co. Field Madras, Oregon.
Well No. 1 Wichman, Sec. 27, T. 11 S, R. 15 E. W. M. W.B. & M.
Signed [Signature]
Date November 6th, 1950 Title Owner
(President, Secretary or Agent)

It is of the greatest importance to have a complete history of the well. Use this form in reporting the history of all important operations at the well, together with the dates thereof, prior to the first production. Include in your report such information as size of hole drilled to cementing or landing depth of casings, number of sacks of cement used in the plugging, number of sacks or number of feet of cement drilled out of casing, depth at which cement plugs started, and depth at which hard cement encountered. If the well was dynamited, give date, size, position and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position and results of pumping or bailing.

Date 8/13/50 Set 372 feet of surface casing, cemented with 150 sacks. Left ten feet of cement in casing.
10/30/50 Plugged hole at 800 feet with fifty sacks of cement.
11/6/50 Plugged top of surface casing, wooden plug and ten sacks of cement.

I.W. LOVE - Wichman #1

November 6th, 1950

From	To	
0	38'	Gravel
38	74'	Shale & streaks of sand
74	346'	Lava (lost circulation)
346	372'	Hard Igneous rock
372	412'	Hard rock
412	457'	Sand (water flow started)
457	522'	Hard rock
522	548'	Sand (water sand)
548	583'	Lime & streaks of sand
583	659'	Lime & shale
659	675'	Shale & sand
675	692'	Hard rock
692	730'	Shale
730	1287'	Sand & shale
1287	1505'	Blue & red shale
1505	1870'	Shale
1870	2040'	Green & blue shale
2040	2162'	Brown & green shale
2162	2181'	Shale
2181	2194'	Hard sand
2194	2196'	Hard sand (cored) core no. 1
2196	2245'	Hard sand
2245	2316'	Sand & shale
2316	2495'	Shale
2495	2564'	Lime & Shale (cored) core no. 2
2564	2609'	Lime & shale
2609	2699'	Shale
		Shale & lime
		Total depth.

Copied from Drillers Log:

Plugged at 800 feet October 30th., 1950, with fifty sacks of cement
Plugged at top of surface casing on November 6th, 1950, with ten sacks of drilling mud, wooden plug, and ten sacks of cement.

Signed by [Signature]
Owner & operator

120.